

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2018

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	692	1,092	15	97	92	2	24	129	169	1	2	57	0
	Flex	.00	.00	.00	.34	.10	.29	.16	.24	.34	.39	.64	.20	.47	0.00
	Rigid	.00	.00	.00	.42	.10	.44	.37	.25	.56	.91	.63	.21	.93	0.00
	GVW	2.3	3.3	6.1	25.2	15.4	26.5	38.9	29.8	40.3	68.0	40.3	37.4	67.0	0.0
E	Num	2	328	530	8	47	46	1	16	79	54	1	1	44	0
	Flex	.00	.00	.00	.38	.10	.20	.06	.25	.23	.28	.03	.30	.38	0.00
	Rigid	.00	.00	.00	.50	.10	.26	.13	.25	.32	.62	.03	.34	.82	0.00
	GVW	2.4	3.3	6.0	26.6	15.4	23.6	28.3	30.5	37.3	56.2	25.5	43.3	67.0	0.0
W	Num	2	668	562	8	50	46	2	9	50	115	1	1	13	0
	Flex	.00	.00	.00	.31	.11	.37	.28	.20	.54	.44	.79	.15	.91	0.00
	Rigid	.00	.00	.00	.36	.11	.60	.59	.24	.97	1.06	.78	.14	1.53	0.00
	GVW	2.3	3.7	6.1	24.2	15.5	28.7	46.8	27.7	45.4	73.7	44.0	34.2	70.0	0.0
E Lane1	Num	2	328	530	8	47	46	1	16	79	54	1	1	44	0
	Flex	.00	.00	.00	.38	.10	.20	.06	.25	.23	.28	.03	.30	.38	0.00
	Rigid	.00	.00	.00	.50	.10	.26	.13	.25	.32	.62	.03	.34	.82	0.00
	GVW	2.4	3.3	6.0	26.6	15.4	23.6	28.3	30.5	37.3	56.2	25.5	43.3	67.0	0.0
W Lane1	Num	2	668	562	8	50	46	2	9	50	115	1	1	13	0
	Flex	.00	.00	.00	.31	.11	.37	.28	.20	.54	.44	.79	.15	.91	0.00
	Rigid	.00	.00	.00	.36	.11	.60	.59	.24	.97	1.06	.78	.14	1.53	0.00
	GVW	2.3	3.7	6.1	24.2	15.5	28.7	46.8	27.7	45.4	73.7	44.0	34.2	70.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2018

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9