

Idaho Transportation Department

Monthly WIM Distribution for Nov-2018

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,148	993	14	77	38	2	24	96	106	2	1	75	0
	Flex	.00	.00	.00	.24	.14	.27	.25	.19	.22	.28	.41	.33	.28	0.00
	Rigid	.00	.00	.00	.31	.14	.37	.42	.20	.32	.68	.40	.34	.52	0.00
	GVW	2.5	3.5	5.9	23.3	16.1	27.0	38.0	28.2	37.5	67.4	39.5	42.3	57.6	0.0
E	Num	1	549	480	7	39	19	1	15	55	31	1	1	65	0
	Flex	.00	.00	.00	.32	.17	.27	.24	.23	.21	.37	.89	.52	.26	0.00
	Rigid	.00	.00	.00	.46	.17	.37	.45	.24	.30	.85	.86	.59	.51	0.00
	GVW	2.3	3.3	5.8	26.7	16.6	27.3	40.0	29.2	36.6	67.5	51.8	58.6	57.8	0.0
W	Num	2	599	512	7	38	20	2	10	41	75	1	1	10	0
	Flex	.00	.00	.00	.18	.11	.28	.20	.11	.24	.26	.23	.32	.41	0.00
	Rigid	.00	.00	.00	.19	.11	.39	.32	.13	.37	.62	.21	.33	.69	0.00
	GVW	1.7	3.6	6.0	20.7	15.7	27.4	37.1	24.3	38.9	67.6	35.4	39.8	58.2	0.0
E Lane1	Num	1	549	480	7	39	19	1	15	55	31	1	1	65	0
	Flex	.00	.00	.00	.32	.17	.27	.24	.23	.21	.37	.89	.52	.26	0.00
	Rigid	.00	.00	.00	.46	.17	.37	.45	.24	.30	.85	.86	.59	.51	0.00
	GVW	2.3	3.3	5.8	26.7	16.6	27.3	40.0	29.2	36.6	67.5	51.8	58.6	57.8	0.0
W Lane1	Num	2	599	512	7	38	20	2	10	41	75	1	1	10	0
	Flex	.00	.00	.00	.18	.11	.28	.20	.11	.24	.26	.23	.32	.41	0.00
	Rigid	.00	.00	.00	.19	.11	.39	.32	.13	.37	.62	.21	.33	.69	0.00
	GVW	1.7	3.6	6.0	20.7	15.7	27.4	37.1	24.3	38.9	67.6	35.4	39.8	58.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2018

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9