

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	998	870	14	57	18	1	22	89	101	2	1	40	0
	Flex	.00	.00	.00	.23	.11	.34	.23	.23	.22	.32	.52	.28	.38	0.00
	Rigid	.00	.00	.00	.29	.11	.45	.36	.23	.32	.71	.50	.28	.81	0.00
	GVW	2.9	3.4	5.8	23.3	16.0	27.8	35.8	29.0	36.6	67.1	43.5	38.8	67.7	0.0
E	Num	1	474	423	8	29	9	1	16	54	32	1	1	27	0
	Flex	.00	.00	.00	.28	.15	.50	.16	.24	.22	.37	.79	.92	.41	0.00
	Rigid	.00	.00	.00	.37	.14	.70	.40	.24	.33	.83	.76	.98	.90	0.00
	GVW	3.1	3.3	5.7	25.0	16.4	31.7	41.8	29.9	35.9	67.4	49.0	63.5	71.4	0.0
W	Num	2	524	447	7	27	10	1	6	35	69	1	1	13	0
	Flex	.00	.00	.00	.17	.09	.20	.32	.21	.23	.30	.34	.18	.36	0.00
	Rigid	.00	.00	.00	.19	.09	.23	.45	.23	.32	.65	.32	.17	.63	0.00
	GVW	2.3	3.6	5.9	20.9	15.6	23.9	37.6	24.5	38.0	67.1	39.6	35.4	59.3	0.0
E Lane1	Num	1	474	423	8	29	9	1	16	54	32	1	1	27	0
	Flex	.00	.00	.00	.28	.15	.50	.16	.24	.22	.37	.79	.92	.41	0.00
	Rigid	.00	.00	.00	.37	.14	.70	.40	.24	.33	.83	.76	.98	.90	0.00
	GVW	3.1	3.3	5.7	25.0	16.4	31.7	41.8	29.9	35.9	67.4	49.0	63.5	71.4	0.0
W Lane1	Num	2	524	447	7	27	10	1	6	35	69	1	1	13	0
	Flex	.00	.00	.00	.17	.09	.20	.32	.21	.23	.30	.34	.18	.36	0.00
	Rigid	.00	.00	.00	.19	.09	.23	.45	.23	.32	.65	.32	.17	.63	0.00
	GVW	2.3	3.6	5.9	20.9	15.6	23.9	37.6	24.5	38.0	67.1	39.6	35.4	59.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2019

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9