

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2019

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,095	995	12	61	33	1	25	107	114	2	2	47	0
	Flex	.00	.00	.00	.20	.08	.24	.22	.22	.18	.23	.40	.14	.35	0.00
	Rigid	.00	.00	.00	.26	.08	.34	.38	.23	.28	.56	.38	.13	.73	0.00
	GVW	2.0	3.4	5.8	22.7	15.6	27.0	38.5	28.7	35.9	64.7	41.3	33.3	66.3	0.0
E	Num	2	521	488	6	29	15	1	18	64	36	1	1	34	0
	Flex	.00	.00	.00	.23	.08	.31	.21	.21	.18	.23	.66	.19	.32	0.00
	Rigid	.00	.00	.00	.32	.08	.45	.33	.22	.28	.50	.62	.19	.71	0.00
	GVW	2.4	3.2	5.6	24.9	16.0	29.4	36.1	29.0	35.6	58.8	50.4	36.5	67.4	0.0
W	Num	2	574	507	6	32	18	1	7	43	78	1	1	13	0
	Flex	.00	.00	.00	.13	.08	.19	.30	.29	.19	.24	.36	.13	.46	0.00
	Rigid	.00	.00	.00	.15	.08	.25	.45	.33	.29	.58	.34	.12	.84	0.00
	GVW	1.4	3.6	5.9	19.5	15.5	25.0	41.8	28.8	36.6	67.6	39.0	32.9	63.6	0.0
E Lane1	Num	2	521	488	6	29	15	1	18	64	36	1	1	34	0
	Flex	.00	.00	.00	.23	.08	.31	.21	.21	.18	.23	.66	.19	.32	0.00
	Rigid	.00	.00	.00	.32	.08	.45	.33	.22	.28	.50	.62	.19	.71	0.00
	GVW	2.4	3.2	5.6	24.9	16.0	29.4	36.1	29.0	35.6	58.8	50.4	36.5	67.4	0.0
W Lane1	Num	2	574	507	6	32	18	1	7	43	78	1	1	13	0
	Flex	.00	.00	.00	.13	.08	.19	.30	.29	.19	.24	.36	.13	.46	0.00
	Rigid	.00	.00	.00	.15	.08	.25	.45	.33	.29	.58	.34	.12	.84	0.00
	GVW	1.4	3.6	5.9	19.5	15.5	25.0	41.8	28.8	36.6	67.6	39.0	32.9	63.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2019

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9