

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2019

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	1,265	1,120	13	81	51	2	27	118	105	2	2	46	0
	Flex	.00	.00	.00	.25	.08	.26	.18	.21	.21	.24	.79	.92	.40	0.00
	Rigid	.00	.00	.00	.31	.08	.41	.36	.22	.33	.57	.75	1.07	.83	0.00
	GVW	1.9	3.4	5.9	24.6	15.8	26.5	36.5	28.3	37.0	65.1	50.7	62.6	66.0	0.0
E	Num	2	611	552	7	39	24	1	17	69	29	1	1	33	0
	Flex	.00	.00	.00	.25	.09	.25	.32	.20	.22	.32	.52	.44	.33	0.00
	Rigid	.00	.00	.00	.32	.08	.38	.54	.20	.33	.74	.49	.50	.81	0.00
	GVW	1.9	3.3	5.8	25.7	16.0	26.1	40.4	28.3	36.7	66.2	47.4	56.2	68.1	0.0
W	Num	3	654	567	6	42	27	1	11	49	75	1	1	13	0
	Flex	.00	.00	.00	.23	.08	.28	.12	.26	.21	.21	1.10	1.63	.56	0.00
	Rigid	.00	.00	.00	.27	.08	.44	.29	.28	.32	.51	1.05	1.88	.84	0.00
	GVW	1.5	3.5	6.0	21.9	15.4	27.0	35.4	27.6	37.4	64.8	55.3	70.3	59.5	0.0
E Lane1	Num	2	611	552	7	39	24	1	17	69	29	1	1	33	0
	Flex	.00	.00	.00	.25	.09	.25	.32	.20	.22	.32	.52	.44	.33	0.00
	Rigid	.00	.00	.00	.32	.08	.38	.54	.20	.33	.74	.49	.50	.81	0.00
	GVW	1.9	3.3	5.8	25.7	16.0	26.1	40.4	28.3	36.7	66.2	47.4	56.2	68.1	0.0
W Lane1	Num	3	654	567	6	42	27	1	11	49	75	1	1	13	0
	Flex	.00	.00	.00	.23	.08	.28	.12	.26	.21	.21	1.10	1.63	.56	0.00
	Rigid	.00	.00	.00	.27	.08	.44	.29	.28	.32	.51	1.05	1.88	.84	0.00
	GVW	1.5	3.5	6.0	21.9	15.4	27.0	35.4	27.6	37.4	64.8	55.3	70.3	59.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2019

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9