

Idaho Transportation Department

Monthly WIM Distribution for May-2019

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	6	1,260	1,074	14	121	31	2	23	110	119	2	2	44	0
	Flex	.00	.00	.00	1.03	.11	.58	.52	.35	.38	.37	.82	.65	.90	0.00
	Rigid	.00	.00	.00	1.46	.11	.82	1.30	.37	.57	.90	.81	.74	2.07	0.00
	GVW	1.7	3.6	6.1	30.7	15.6	29.8	49.0	29.6	39.2	69.2	49.5	53.6	75.1	0.0
E	Num	3	602	519	7	64	15	1	15	67	34	1	1	32	0
	Flex	.00	.00	.00	1.50	.12	.61	.62	.40	.39	.48	.82	.21	.94	0.00
	Rigid	.00	.00	.00	2.13	.12	.89	1.44	.41	.60	1.16	.79	.29	2.35	0.00
	GVW	2.0	3.5	6.1	34.0	15.4	31.9	53.1	30.7	38.6	66.6	51.4	46.2	79.3	0.0
W	Num	4	658	554	7	57	16	2	9	43	85	1	1	12	0
	Flex	.00	.00	.00	.40	.10	.57	.30	.22	.36	.32	1.02	.95	.73	0.00
	Rigid	.00	.00	.00	.50	.10	.77	.90	.25	.54	.80	1.04	1.08	1.18	0.00
	GVW	1.2	3.6	6.2	25.3	15.8	28.0	45.6	25.0	40.4	70.3	48.0	56.7	63.1	0.0
E Lane1	Num	3	602	519	7	64	15	1	15	67	34	1	1	32	0
	Flex	.00	.00	.00	1.50	.12	.61	.62	.40	.39	.48	.82	.21	.94	0.00
	Rigid	.00	.00	.00	2.13	.12	.89	1.44	.41	.60	1.16	.79	.29	2.35	0.00
	GVW	2.0	3.5	6.1	34.0	15.4	31.9	53.1	30.7	38.6	66.6	51.4	46.2	79.3	0.0
W Lane1	Num	4	658	554	7	57	16	2	9	43	85	1	1	12	0
	Flex	.00	.00	.00	.40	.10	.57	.30	.22	.36	.32	1.02	.95	.73	0.00
	Rigid	.00	.00	.00	.50	.10	.77	.90	.25	.54	.80	1.04	1.08	1.18	0.00
	GVW	1.2	3.6	6.2	25.3	15.8	28.0	45.6	25.0	40.4	70.3	48.0	56.7	63.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2019

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9