

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2019

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	8	1,271	1,007	11	303	35	3	32	105	112	2	1	49	0
	Flex	.00	.00	.00	1.79	.19	1.69	.89	1.15	1.24	1.36	2.92	.37	2.01	0.00
	Rigid	.00	.00	.00	2.80	.20	2.54	2.59	1.40	2.08	3.46	3.09	.39	4.90	0.00
	GVW	2.2	4.2	6.4	36.8	16.1	38.6	58.7	34.8	47.7	85.8	66.5	43.2	89.9	0.0
E	Num	4	607	506	6	135	18	2	19	63	32	1	1	36	0
	Flex	.00	.00	.00	1.72	.19	1.48	.92	1.07	1.09	1.35	1.22	.33	2.03	0.00
	Rigid	.00	.00	.00	2.83	.20	2.47	2.97	1.27	1.92	3.44	1.19	.38	5.38	0.00
	GVW	2.4	4.0	6.2	36.6	16.1	38.0	55.3	33.7	44.4	76.7	56.9	47.5	94.3	0.0
W	Num	5	664	501	5	167	17	2	13	41	80	1	1	13	0
	Flex	.00	.00	.00	1.62	.18	2.06	.80	1.09	1.47	1.37	4.08	.37	1.99	0.00
	Rigid	.00	.00	.00	2.21	.19	2.92	2.23	1.40	2.36	3.48	4.40	.38	3.72	0.00
	GVW	2.0	4.3	6.7	33.1	16.1	40.5	58.9	34.2	53.2	89.3	72.4	37.9	76.6	0.0
E Lane1	Num	4	607	506	6	135	18	2	19	63	32	1	1	36	0
	Flex	.00	.00	.00	1.72	.19	1.48	.92	1.07	1.09	1.35	1.22	.33	2.03	0.00
	Rigid	.00	.00	.00	2.83	.20	2.47	2.97	1.27	1.92	3.44	1.19	.38	5.38	0.00
	GVW	2.4	4.0	6.2	36.6	16.1	38.0	55.3	33.7	44.4	76.7	56.9	47.5	94.3	0.0
W Lane1	Num	5	664	501	5	167	17	2	13	41	80	1	1	13	0
	Flex	.00	.00	.00	1.62	.18	2.06	.80	1.09	1.47	1.37	4.08	.37	1.99	0.00
	Rigid	.00	.00	.00	2.21	.19	2.92	2.23	1.40	2.36	3.48	4.40	.38	3.72	0.00
	GVW	2.0	4.3	6.7	33.1	16.1	40.5	58.9	34.2	53.2	89.3	72.4	37.9	76.6	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jun-2019

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9