

Idaho Transportation Department

Monthly WIM Distribution for Jul-2019

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	6	1,099	891	9	273	26	3	30	95	105	2	2	47	0
	Flex	.00	.00	.00	1.77	.21	2.06	2.74	.97	1.35	1.63	5.12	2.07	2.52	0.00
	Rigid	.00	.00	.00	2.42	.22	3.28	8.54	1.15	2.24	4.12	5.97	2.31	5.49	0.00
	GVW	2.0	4.2	6.1	34.4	16.1	38.3	79.4	30.9	44.2	85.8	56.5	63.0	85.9	0.0
E	Num	3	502	450	5	100	12	2	18	53	30	1	0	34	0
	Flex	.00	.00	.00	1.29	.18	1.59	2.75	.82	.81	1.30	1.05	0.00	2.25	0.00
	Rigid	.00	.00	.00	1.89	.19	2.80	7.31	.93	1.40	3.41	1.14	0.00	5.36	0.00
	GVW	2.6	4.0	5.7	31.5	15.8	35.0	65.5	29.2	37.1	75.5	41.5	0.0	85.6	0.0
W	Num	3	597	441	5	172	15	2	13	41	75	1	2	13	0
	Flex	.00	.00	.00	2.51	.22	2.52	2.57	1.14	2.19	1.79	13.88	2.07	3.22	0.00
	Rigid	.00	.00	.00	3.38	.23	3.59	8.30	1.43	3.59	4.46	16.43	2.31	5.49	0.00
	GVW	1.4	4.3	6.4	40.7	16.3	40.9	83.0	33.1	54.4	90.1	84.0	63.0	84.3	0.0
E Lane1	Num	3	502	450	5	100	12	2	18	53	30	1	0	34	0
	Flex	.00	.00	.00	1.29	.18	1.59	2.75	.82	.81	1.30	1.05	0.00	2.25	0.00
	Rigid	.00	.00	.00	1.89	.19	2.80	7.31	.93	1.40	3.41	1.14	0.00	5.36	0.00
	GVW	2.6	4.0	5.7	31.5	15.8	35.0	65.5	29.2	37.1	75.5	41.5	0.0	85.6	0.0
W Lane1	Num	3	597	441	5	172	15	2	13	41	75	1	2	13	0
	Flex	.00	.00	.00	2.51	.22	2.52	2.57	1.14	2.19	1.79	13.88	2.07	3.22	0.00
	Rigid	.00	.00	.00	3.38	.23	3.59	8.30	1.43	3.59	4.46	16.43	2.31	5.49	0.00
	GVW	1.4	4.3	6.4	40.7	16.3	40.9	83.0	33.1	54.4	90.1	84.0	63.0	84.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2019

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9