

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2019

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	5	1,059	906	9	255	46	2	30	111	113	1	1	59	0
	Flex	.00	.00	.00	2.14	.23	1.72	1.07	.93	1.18	1.44	2.00	.66	2.78	0.00
	Rigid	.00	.00	.00	3.15	.24	2.91	3.16	1.09	2.04	3.66	2.13	.77	5.94	0.00
	GVW	1.7	4.1	6.0	34.0	16.3	37.8	57.4	32.3	43.7	79.7	48.5	49.5	88.3	0.0
E	Num	2	513	468	4	98	22	1	19	62	34	1	1	39	0
	Flex	.00	.00	.00	1.99	.20	1.46	2.04	.78	.97	1.37	.28	.28	2.47	0.00
	Rigid	.00	.00	.00	3.07	.21	2.64	5.60	.89	1.84	3.52	.27	.39	5.71	0.00
	GVW	2.0	3.9	5.7	33.2	16.1	37.0	67.6	32.7	40.8	78.0	35.5	42.4	89.5	0.0
W	Num	3	546	438	5	158	24	2	11	49	79	1	1	19	0
	Flex	.00	.00	.00	2.22	.24	1.99	.91	1.08	1.47	1.51	3.38	.96	4.39	0.00
	Rigid	.00	.00	.00	3.12	.25	3.24	2.75	1.34	2.35	3.80	3.66	1.05	7.47	0.00
	GVW	1.5	4.3	6.3	34.2	16.4	39.1	53.4	30.0	48.0	81.1	58.1	52.5	84.3	0.0
E Lane1	Num	2	513	468	4	98	22	1	19	62	34	1	1	39	0
	Flex	.00	.00	.00	1.99	.20	1.46	2.04	.78	.97	1.37	.28	.28	2.47	0.00
	Rigid	.00	.00	.00	3.07	.21	2.64	5.60	.89	1.84	3.52	.27	.39	5.71	0.00
	GVW	2.0	3.9	5.7	33.2	16.1	37.0	67.6	32.7	40.8	78.0	35.5	42.4	89.5	0.0
W Lane1	Num	3	546	438	5	158	24	2	11	49	79	1	1	19	0
	Flex	.00	.00	.00	2.22	.24	1.99	.91	1.08	1.47	1.51	3.38	.96	4.39	0.00
	Rigid	.00	.00	.00	3.12	.25	3.24	2.75	1.34	2.35	3.80	3.66	1.05	7.47	0.00
	GVW	1.5	4.3	6.3	34.2	16.4	39.1	53.4	30.0	48.0	81.1	58.1	52.5	84.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Aug-2019

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9