

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	1,152	1,019	16	176	82	2	28	126	121	2	1	49	0
	Flex	.00	.00	.00	1.08	.16	.92	.54	.57	.73	.75	1.71	.44	1.49	0.00
	Rigid	.00	.00	.00	1.70	.16	1.56	1.42	.66	1.33	1.93	1.79	.51	3.23	0.00
	GVW	1.8	3.9	6.2	31.4	15.7	33.3	51.8	32.0	44.0	77.6	55.9	54.6	82.6	0.0
E	Num	2	550	498	8	82	41	1	19	71	36	1	1	36	0
	Flex	.00	.00	.00	.74	.15	.67	.43	.48	.56	.93	.78	.61	1.26	0.00
	Rigid	.00	.00	.00	1.08	.16	1.10	1.32	.52	.97	2.39	.76	.73	3.07	0.00
	GVW	2.0	3.8	6.1	30.3	15.8	30.6	52.2	32.1	41.3	79.1	48.9	60.8	84.5	0.0
W	Num	3	601	521	8	94	41	1	9	54	85	1	1	13	0
	Flex	.00	.00	.00	1.53	.16	1.20	.61	.63	.97	.67	2.02	.17	2.17	0.00
	Rigid	.00	.00	.00	2.39	.17	2.10	1.55	.79	1.81	1.74	2.13	.20	3.58	0.00
	GVW	1.8	4.0	6.4	32.4	15.7	36.2	53.1	29.4	47.8	77.2	58.0	45.6	75.2	0.0
E Lane1	Num	2	550	498	8	82	41	1	19	71	36	1	1	36	0
	Flex	.00	.00	.00	.74	.15	.67	.43	.48	.56	.93	.78	.61	1.26	0.00
	Rigid	.00	.00	.00	1.08	.16	1.10	1.32	.52	.97	2.39	.76	.73	3.07	0.00
	GVW	2.0	3.8	6.1	30.3	15.8	30.6	52.2	32.1	41.3	79.1	48.9	60.8	84.5	0.0
W Lane1	Num	3	601	521	8	94	41	1	9	54	85	1	1	13	0
	Flex	.00	.00	.00	1.53	.16	1.20	.61	.63	.97	.67	2.02	.17	2.17	0.00
	Rigid	.00	.00	.00	2.39	.17	2.10	1.55	.79	1.81	1.74	2.13	.20	3.58	0.00
	GVW	1.8	4.0	6.4	32.4	15.7	36.2	53.1	29.4	47.8	77.2	58.0	45.6	75.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9