

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2019

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	1,128	1,092	14	83	69	1	26	148	149	1	1	50	0
	Flex	.00	.00	.00	.30	.08	.33	.16	.25	.31	.32	.56	.12	.50	0.00
	Rigid	.00	.00	.00	.40	.08	.50	.38	.26	.55	.77	.55	.12	1.04	0.00
	GVW	1.9	3.5	6.0	25.4	15.6	28.1	36.1	29.5	39.3	66.7	46.9	33.6	71.2	0.0
E	Num	1	536	535	7	40	34	1	17	85	52	1	1	37	0
	Flex	.00	.00	.00	.30	.09	.30	.10	.27	.23	.37	.61	.03	.45	0.00
	Rigid	.00	.00	.00	.41	.09	.43	.23	.28	.37	.86	.57	.03	1.02	0.00
	GVW	1.6	3.4	5.9	25.7	15.8	27.1	34.2	30.6	36.3	64.9	48.8	25.8	71.9	0.0
W	Num	2	611	574	7	43	35	1	10	66	97	1	1	12	0
	Flex	.00	.00	.00	.25	.08	.33	.23	.21	.42	.30	.50	.19	.69	0.00
	Rigid	.00	.00	.00	.32	.07	.55	.58	.23	.78	.71	.50	.19	1.14	0.00
	GVW	1.8	3.7	6.1	24.2	15.4	28.4	37.8	27.3	43.6	67.6	44.4	38.1	68.7	0.0
E Lane1	Num	1	536	535	7	40	34	1	17	85	52	1	1	37	0
	Flex	.00	.00	.00	.30	.09	.30	.10	.27	.23	.37	.61	.03	.45	0.00
	Rigid	.00	.00	.00	.41	.09	.43	.23	.28	.37	.86	.57	.03	1.02	0.00
	GVW	1.6	3.4	5.9	25.7	15.8	27.1	34.2	30.6	36.3	64.9	48.8	25.8	71.9	0.0
W Lane1	Num	2	611	574	7	43	35	1	10	66	97	1	1	12	0
	Flex	.00	.00	.00	.25	.08	.33	.23	.21	.42	.30	.50	.19	.69	0.00
	Rigid	.00	.00	.00	.32	.07	.55	.58	.23	.78	.71	.50	.19	1.14	0.00
	GVW	1.8	3.7	6.1	24.2	15.4	28.4	37.8	27.3	43.6	67.6	44.4	38.1	68.7	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2019

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9