

Idaho Transportation Department

Monthly WIM Distribution for Nov-2019

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,007	998	12	62	41	2	24	114	107	1	2	44	0
	Flex	.00	.00	.00	.20	.09	.25	.18	.20	.18	.25	.39	.13	.36	0.00
	Rigid	.00	.00	.00	.25	.09	.35	.28	.21	.27	.60	.37	.15	.70	0.00
	GVW	1.4	3.4	5.8	22.2	15.3	26.6	34.0	28.2	35.5	65.5	44.3	40.8	64.9	0.0
E	Num	2	479	490	6	30	21	1	16	65	33	1	1	34	0
	Flex	.00	.00	.00	.24	.11	.30	.26	.22	.18	.29	.46	.19	.30	0.00
	Rigid	.00	.00	.00	.31	.10	.42	.39	.23	.27	.66	.44	.24	.64	0.00
	GVW	2.3	3.2	5.6	24.1	15.6	28.4	33.2	28.9	35.0	65.1	46.9	48.6	65.8	0.0
W	Num	2	528	507	6	32	21	1	9	49	74	1	1	11	0
	Flex	.00	.00	.00	.17	.07	.21	.21	.14	.17	.23	.32	.09	.58	0.00
	Rigid	.00	.00	.00	.20	.07	.29	.33	.16	.26	.56	.30	.10	.90	0.00
	GVW	1.2	3.6	5.9	21.3	15.0	25.3	36.8	26.0	36.3	65.6	39.8	37.0	61.8	0.0
E Lane1	Num	2	479	490	6	30	21	1	16	65	33	1	1	34	0
	Flex	.00	.00	.00	.24	.11	.30	.26	.22	.18	.29	.46	.19	.30	0.00
	Rigid	.00	.00	.00	.31	.10	.42	.39	.23	.27	.66	.44	.24	.64	0.00
	GVW	2.3	3.2	5.6	24.1	15.6	28.4	33.2	28.9	35.0	65.1	46.9	48.6	65.8	0.0
W Lane1	Num	2	528	507	6	32	21	1	9	49	74	1	1	11	0
	Flex	.00	.00	.00	.17	.07	.21	.21	.14	.17	.23	.32	.09	.58	0.00
	Rigid	.00	.00	.00	.20	.07	.29	.33	.16	.26	.56	.30	.10	.90	0.00
	GVW	1.2	3.6	5.9	21.3	15.0	25.3	36.8	26.0	36.3	65.6	39.8	37.0	61.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2019

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9