

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2020

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	876	832	11	66	21	2	22	95	88	1	1	29	0
	Flex	.00	.00	.00	.29	.10	.30	.12	.21	.20	.35	.55	.43	.42	0.00
	Rigid	.00	.00	.00	.39	.10	.41	.18	.21	.31	.74	.51	.43	.87	0.00
	GVW	3.1	3.5	5.8	24.4	15.5	28.5	31.0	28.4	35.8	66.6	46.8	52.3	67.7	0.0
E	Num	2	418	409	6	32	10	2	16	54	26	1	0	23	0
	Flex	.00	.00	.00	.41	.11	.43	.12	.22	.24	.48	.68	0.00	.42	0.00
	Rigid	.00	.00	.00	.58	.11	.62	.19	.22	.37	1.07	.64	0.00	.92	0.00
	GVW	3.5	3.3	5.7	27.6	16.0	31.9	29.5	29.2	36.5	72.6	52.3	0.0	71.0	0.0
W	Num	1	459	423	6	34	12	1	6	41	62	1	1	7	0
	Flex	.00	.00	.00	.14	.08	.19	.09	.16	.16	.29	.48	.43	.37	0.00
	Rigid	.00	.00	.00	.14	.08	.25	.14	.17	.23	.60	.45	.43	.55	0.00
	GVW	3.6	3.6	5.9	18.9	15.0	25.8	29.4	25.0	35.1	64.0	43.1	52.3	52.1	0.0
E Lane1	Num	2	418	409	6	32	10	2	16	54	26	1	0	23	0
	Flex	.00	.00	.00	.41	.11	.43	.12	.22	.24	.48	.68	0.00	.42	0.00
	Rigid	.00	.00	.00	.58	.11	.62	.19	.22	.37	1.07	.64	0.00	.92	0.00
	GVW	3.5	3.3	5.7	27.6	16.0	31.9	29.5	29.2	36.5	72.6	52.3	0.0	71.0	0.0
W Lane1	Num	1	459	423	6	34	12	1	6	41	62	1	1	7	0
	Flex	.00	.00	.00	.14	.08	.19	.09	.16	.16	.29	.48	.43	.37	0.00
	Rigid	.00	.00	.00	.14	.08	.25	.14	.17	.23	.60	.45	.43	.55	0.00
	GVW	3.6	3.6	5.9	18.9	15.0	25.8	29.4	25.0	35.1	64.0	43.1	52.3	52.1	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jan-2020

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9