

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,008	898	11	74	24	1	21	96	91	2	2	36	0
	Flex	.00	.00	.00	.26	.10	.24	.16	.18	.21	.30	.55	.55	.44	0.00
	Rigid	.00	.00	.00	.34	.10	.32	.25	.19	.33	.65	.52	.60	.94	0.00
	GVW	1.3	3.5	5.8	23.8	15.6	26.8	36.2	28.2	36.3	65.4	47.0	45.3	68.0	0.0
E	Num	1	479	441	6	35	11	1	15	54	30	2	1	27	0
	Flex	.00	.00	.00	.34	.12	.36	.23	.20	.27	.40	.62	1.08	.43	0.00
	Rigid	.00	.00	.00	.45	.11	.50	.28	.20	.43	.89	.58	1.16	1.02	0.00
	GVW	2.0	3.3	5.8	25.6	16.1	30.2	31.0	29.1	38.1	70.3	50.4	61.9	73.0	0.0
W	Num	2	529	457	5	38	14	1	7	42	61	1	1	10	0
	Flex	.00	.00	.00	.12	.09	.16	.10	.13	.14	.24	.53	.02	.46	0.00
	Rigid	.00	.00	.00	.13	.09	.21	.19	.15	.21	.54	.49	.03	.71	0.00
	GVW	1.0	3.6	5.9	19.9	15.3	24.7	35.4	25.6	34.2	63.1	44.8	28.7	52.5	0.0
E Lane1	Num	1	479	441	6	35	11	1	15	54	30	2	1	27	0
	Flex	.00	.00	.00	.34	.12	.36	.23	.20	.27	.40	.62	1.08	.43	0.00
	Rigid	.00	.00	.00	.45	.11	.50	.28	.20	.43	.89	.58	1.16	1.02	0.00
	GVW	2.0	3.3	5.8	25.6	16.1	30.2	31.0	29.1	38.1	70.3	50.4	61.9	73.0	0.0
W Lane1	Num	2	529	457	5	38	14	1	7	42	61	1	1	10	0
	Flex	.00	.00	.00	.12	.09	.16	.10	.13	.14	.24	.53	.02	.46	0.00
	Rigid	.00	.00	.00	.13	.09	.21	.19	.15	.21	.54	.49	.03	.71	0.00
	GVW	1.0	3.6	5.9	19.9	15.3	24.7	35.4	25.6	34.2	63.1	44.8	28.7	52.5	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9