

Idaho Transportation Department

Monthly WIM Distribution for Apr-2020

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	859	948	10	77	42	2	24	120	117	2	2	46	0
	Flex	.00	.00	.00	.34	.11	.37	.42	.23	.24	.28	.69	.15	.45	0.00
	Rigid	.00	.00	.00	.44	.11	.58	.70	.23	.39	.66	.66	.16	.96	0.00
	GVW	1.0	3.5	6.0	25.4	15.9	29.6	44.3	28.1	36.6	65.3	49.8	36.0	67.6	0.0
E	Num	2	409	469	5	37	18	1	17	71	36	1	1	33	0
	Flex	.00	.00	.00	.34	.12	.32	.58	.25	.26	.42	.64	.10	.39	0.00
	Rigid	.00	.00	.00	.46	.12	.45	.87	.25	.41	.97	.60	.11	.92	0.00
	GVW	1.3	3.3	5.9	27.2	16.2	27.8	46.1	29.2	36.3	66.8	51.7	34.8	68.0	0.0
W	Num	3	450	479	5	40	24	2	7	48	81	1	1	13	0
	Flex	.00	.00	.00	.30	.10	.40	.37	.18	.22	.22	.74	.20	.67	0.00
	Rigid	.00	.00	.00	.33	.10	.65	.66	.19	.36	.52	.71	.21	1.03	0.00
	GVW	1.0	3.6	6.1	21.2	15.8	30.8	44.2	25.8	36.9	64.5	47.9	37.2	63.1	0.0
E Lane1	Num	2	409	469	5	37	18	1	17	71	36	1	1	33	0
	Flex	.00	.00	.00	.34	.12	.32	.58	.25	.26	.42	.64	.10	.39	0.00
	Rigid	.00	.00	.00	.46	.12	.45	.87	.25	.41	.97	.60	.11	.92	0.00
	GVW	1.3	3.3	5.9	27.2	16.2	27.8	46.1	29.2	36.3	66.8	51.7	34.8	68.0	0.0
W Lane1	Num	3	450	479	5	40	24	2	7	48	81	1	1	13	0
	Flex	.00	.00	.00	.30	.10	.40	.37	.18	.22	.22	.74	.20	.67	0.00
	Rigid	.00	.00	.00	.33	.10	.65	.66	.19	.36	.52	.71	.21	1.03	0.00
	GVW	1.0	3.6	6.1	21.2	15.8	30.8	44.2	25.8	36.9	64.5	47.9	37.2	63.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2020

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9