

# Idaho Transportation Department

## Monthly WIM Distribution for May-2020

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	1,062	1,072	11	126	27	1	26	111	121	2	1	46	0
	Flex	.00	.00	.00	.52	.10	.55	.69	.39	.45	.45	1.14	.37	.85	0.00
	Rigid	.00	.00	.00	.74	.10	.82	1.16	.42	.71	1.11	1.12	.38	1.97	0.00
	GVW	1.4	3.6	6.2	27.4	15.7	29.9	46.5	29.5	39.1	70.0	52.3	40.5	76.4	0.0
E	Num	2	512	530	5	63	13	1	18	68	33	1	1	35	0
	Flex	.00	.00	.00	.73	.10	.76	1.10	.39	.48	.61	.65	.16	.72	0.00
	Rigid	.00	.00	.00	1.17	.11	1.26	1.75	.40	.77	1.41	.61	.18	1.90	0.00
	GVW	1.5	3.5	6.1	30.8	15.7	34.0	52.3	30.1	39.2	66.6	48.6	37.9	77.3	0.0
W	Num	3	550	542	6	64	15	1	8	44	88	1	1	11	0
	Flex	.00	.00	.00	.44	.09	.42	.09	.40	.38	.39	1.35	.62	1.10	0.00
	Rigid	.00	.00	.00	.57	.09	.53	.28	.44	.58	1.00	1.35	.62	1.85	0.00
	GVW	1.5	3.7	6.3	25.5	15.7	27.4	37.5	27.9	39.0	71.3	53.3	48.9	68.9	0.0
E Lane1	Num	2	512	530	5	63	13	1	18	68	33	1	1	35	0
	Flex	.00	.00	.00	.73	.10	.76	1.10	.39	.48	.61	.65	.16	.72	0.00
	Rigid	.00	.00	.00	1.17	.11	1.26	1.75	.40	.77	1.41	.61	.18	1.90	0.00
	GVW	1.5	3.5	6.1	30.8	15.7	34.0	52.3	30.1	39.2	66.6	48.6	37.9	77.3	0.0
W Lane1	Num	3	550	542	6	64	15	1	8	44	88	1	1	11	0
	Flex	.00	.00	.00	.44	.09	.42	.09	.40	.38	.39	1.35	.62	1.10	0.00
	Rigid	.00	.00	.00	.57	.09	.53	.28	.44	.58	1.00	1.35	.62	1.85	0.00
	GVW	1.5	3.7	6.3	25.5	15.7	27.4	37.5	27.9	39.0	71.3	53.3	48.9	68.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for May-2020

Site names: 00155  
 County: Twin Falls  
 Funct Class: R Minor Arterial - Other  
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9