

Idaho Transportation Department

Monthly WIM Distribution for Jun-2020

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	1,058	954	11	260	27	2	27	110	109	1	1	39	0
	Flex	.00	.00	.00	1.50	.19	2.45	.30	.84	1.01	.99	2.09	1.13	1.99	0.00
	Rigid	.00	.00	.00	2.34	.21	3.57	.64	.95	1.76	2.48	2.30	1.28	5.17	0.00
	GVW	1.8	4.1	6.5	35.7	16.2	39.8	39.1	33.6	46.6	79.3	51.1	47.6	96.3	0.0
E	Num	2	514	474	5	127	12	1	18	64	30	1	1	30	0
	Flex	.00	.00	.00	2.36	.19	2.82	.07	.90	1.11	1.56	1.06	.02	2.04	0.00
	Rigid	.00	.00	.00	3.95	.20	4.36	.23	1.00	1.97	3.96	1.02	.02	5.67	0.00
	GVW	1.9	4.0	6.3	41.5	16.0	45.4	29.6	33.9	46.6	81.5	51.8	25.3	101.9	0.0
W	Num	3	544	480	6	133	16	1	9	46	79	1	1	8	0
	Flex	.00	.00	.00	.98	.19	1.28	.45	.67	.88	.80	3.94	1.87	1.75	0.00
	Rigid	.00	.00	.00	1.37	.20	1.83	.77	.78	1.45	1.99	4.52	2.12	3.20	0.00
	GVW	1.6	4.2	6.6	32.4	16.3	34.8	41.0	32.2	46.6	79.0	57.5	62.6	75.3	0.0
E Lane1	Num	2	514	474	5	127	12	1	18	64	30	1	1	30	0
	Flex	.00	.00	.00	2.36	.19	2.82	.07	.90	1.11	1.56	1.06	.02	2.04	0.00
	Rigid	.00	.00	.00	3.95	.20	4.36	.23	1.00	1.97	3.96	1.02	.02	5.67	0.00
	GVW	1.9	4.0	6.3	41.5	16.0	45.4	29.6	33.9	46.6	81.5	51.8	25.3	101.9	0.0
W Lane1	Num	3	544	480	6	133	16	1	9	46	79	1	1	8	0
	Flex	.00	.00	.00	.98	.19	1.28	.45	.67	.88	.80	3.94	1.87	1.75	0.00
	Rigid	.00	.00	.00	1.37	.20	1.83	.77	.78	1.45	1.99	4.52	2.12	3.20	0.00
	GVW	1.6	4.2	6.6	32.4	16.3	34.8	41.0	32.2	46.6	79.0	57.5	62.6	75.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2020

Site names: 00155
 County: Twin Falls
 Funct Class: R Minor Arterial - Other
 Location: US-30 2.1 Mi. E of Main St

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9