

Idaho Transportation Department

Monthly WIM Distribution for Apr-2019

Site names: 00156
 County: Butte
 Funct Class: R Minor Arterial - Other
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	218	216	3	8	7	1	9	45	23	2	1	38	0
	Flex	.00	.00	.00	.51	1.37	.95	.28	.57	1.41	.88	.90	.92	2.40	0.00
	Rigid	.00	.00	.00	.64	1.53	1.47	.34	.81	2.27	1.99	1.03	1.11	3.39	0.00
	GVW	1.8	3.9	4.2	27.8	21.8	30.7	24.0	22.0	53.6	68.6	27.4	37.8	70.9	0.0
E	Num	1	117	110	2	3	4	1	5	21	10	1	1	19	0
	Flex	.00	.00	.00	.45	.58	.43	.22	.17	.66	.50	.08	.12	.42	0.00
	Rigid	.00	.00	.00	.57	.62	.72	.21	.19	1.07	.99	.08	.12	.55	0.00
	GVW	2.9	4.0	4.5	29.3	18.1	25.8	23.1	22.1	48.7	57.2	22.0	30.6	42.6	0.0
W	Num	1	101	106	1	5	4	1	4	24	13	2	1	19	0
	Flex	.00	.00	.00	.62	1.96	1.22	.56	1.06	2.08	1.16	1.28	6.33	4.40	0.00
	Rigid	.00	.00	.00	.75	2.23	1.83	1.02	1.59	3.35	2.71	1.46	8.20	6.25	0.00
	GVW	1.8	3.7	4.0	25.3	24.1	31.2	35.3	21.6	57.4	76.1	26.5	72.2	99.1	0.0
E Lane1	Num	1	117	110	2	3	4	1	5	21	10	1	1	19	0
	Flex	.00	.00	.00	.45	.58	.43	.22	.17	.66	.50	.08	.12	.42	0.00
	Rigid	.00	.00	.00	.57	.62	.72	.21	.19	1.07	.99	.08	.12	.55	0.00
	GVW	2.9	4.0	4.5	29.3	18.1	25.8	23.1	22.1	48.7	57.2	22.0	30.6	42.6	0.0
W Lane1	Num	1	101	106	1	5	4	1	4	24	13	2	1	19	0
	Flex	.00	.00	.00	.62	1.96	1.22	.56	1.06	2.08	1.16	1.28	6.33	4.40	0.00
	Rigid	.00	.00	.00	.75	2.23	1.83	1.02	1.59	3.35	2.71	1.46	8.20	6.25	0.00
	GVW	1.8	3.7	4.0	25.3	24.1	31.2	35.3	21.6	57.4	76.1	26.5	72.2	99.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2019

Site names: 00156
 County: Butte
 Funct Class: R Minor Arterial - Other
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9