

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2019

Site names: 00156  
 County: Butte  
 Funct Class: R Minor Arterial - Other  
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	300	315	2	11	4	2	13	39	18	3	1	25	0
	Flex	.00	.00	.00	.92	1.32	.81	2.02	.66	1.64	.69	.05	.96	2.07	0.00
	Rigid	.00	.00	.00	1.32	1.48	1.05	2.35	.75	2.72	1.65	.07	1.01	2.82	0.00
	GVW	2.6	3.9	4.1	32.9	21.6	23.6	32.1	21.4	54.5	66.9	20.5	47.6	71.2	0.0
E	Num	1	152	155	1	5	2	1	6	18	9	2	1	13	0
	Flex	.00	.00	.00	1.15	.75	.97	1.44	.31	.94	.48	.03	.51	1.43	0.00
	Rigid	.00	.00	.00	1.69	.79	1.51	1.59	.32	1.54	.97	.04	.56	1.70	0.00
	GVW	2.5	4.0	4.0	41.9	20.6	30.8	31.9	22.5	53.7	56.6	21.4	41.0	59.2	0.0
W	Num	2	148	160	1	6	3	1	7	21	9	2	1	12	0
	Flex	.00	.00	.00	.69	1.74	.94	2.52	.88	2.27	.88	.08	.80	2.60	0.00
	Rigid	.00	.00	.00	.90	1.98	1.14	2.95	1.02	3.77	2.22	.12	.82	3.78	0.00
	GVW	2.2	3.8	4.2	23.8	22.4	21.8	32.5	20.7	55.3	75.3	20.0	45.8	82.9	0.0
E Lane1	Num	1	152	155	1	5	2	1	6	18	9	2	1	13	0
	Flex	.00	.00	.00	1.15	.75	.97	1.44	.31	.94	.48	.03	.51	1.43	0.00
	Rigid	.00	.00	.00	1.69	.79	1.51	1.59	.32	1.54	.97	.04	.56	1.70	0.00
	GVW	2.5	4.0	4.0	41.9	20.6	30.8	31.9	22.5	53.7	56.6	21.4	41.0	59.2	0.0
W Lane1	Num	2	148	160	1	6	3	1	7	21	9	2	1	12	0
	Flex	.00	.00	.00	.69	1.74	.94	2.52	.88	2.27	.88	.08	.80	2.60	0.00
	Rigid	.00	.00	.00	.90	1.98	1.14	2.95	1.02	3.77	2.22	.12	.82	3.78	0.00
	GVW	2.2	3.8	4.2	23.8	22.4	21.8	32.5	20.7	55.3	75.3	20.0	45.8	82.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2019

Site names: 00156  
 County: Butte  
 Funct Class: R Minor Arterial - Other  
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 5  
 Daily Factor Grp: 3  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9