

Idaho Transportation Department

Monthly WIM Distribution for Nov-2019

Site names: 00156
 County: Butte
 Funct Class: R Minor Arterial - Other
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	1	198	227	2	6	3	2	8	40	21	2	1	39	0
	Flex	.00	.00	.00	1.21	1.61	.78	1.02	.41	1.42	1.02	.53	.53	1.70	0.00
	Rigid	.00	.00	.00	1.87	1.82	1.17	1.41	.50	2.25	2.42	1.14	.60	2.47	0.00
	GVW	2.2	3.5	3.7	39.3	22.6	26.1	30.1	23.7	52.7	70.2	26.9	30.8	64.9	0.0
E	Num	1	96	111	1	3	2	2	4	19	10	1	2	19	0
	Flex	.00	.00	.00	2.11	.65	.41	.57	.43	.91	.63	1.15	.40	.47	0.00
	Rigid	.00	.00	.00	3.44	.70	.63	.62	.48	1.40	1.15	2.36	.45	.59	0.00
	GVW	4.2	3.4	3.9	50.8	19.1	22.5	28.9	25.8	49.6	57.0	37.6	46.0	48.9	0.0
W	Num	1	102	116	1	4	2	1	4	21	11	2	1	19	0
	Flex	.00	.00	.00	.06	1.95	.94	1.58	.45	2.02	1.40	.04	.52	2.82	0.00
	Rigid	.00	.00	.00	.09	2.23	1.45	2.32	.58	3.28	3.66	.06	.61	4.19	0.00
	GVW	2.1	3.5	3.6	23.0	23.8	27.2	35.1	22.6	56.2	82.2	20.3	11.7	78.9	0.0
E Lane1	Num	1	96	111	1	3	2	2	4	19	10	1	2	19	0
	Flex	.00	.00	.00	2.11	.65	.41	.57	.43	.91	.63	1.15	.40	.47	0.00
	Rigid	.00	.00	.00	3.44	.70	.63	.62	.48	1.40	1.15	2.36	.45	.59	0.00
	GVW	4.2	3.4	3.9	50.8	19.1	22.5	28.9	25.8	49.6	57.0	37.6	46.0	48.9	0.0
W Lane1	Num	1	102	116	1	4	2	1	4	21	11	2	1	19	0
	Flex	.00	.00	.00	.06	1.95	.94	1.58	.45	2.02	1.40	.04	.52	2.82	0.00
	Rigid	.00	.00	.00	.09	2.23	1.45	2.32	.58	3.28	3.66	.06	.61	4.19	0.00
	GVW	2.1	3.5	3.6	23.0	23.8	27.2	35.1	22.6	56.2	82.2	20.3	11.7	78.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2019

Site names: 00156
 County: Butte
 Funct Class: R Minor Arterial - Other
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 5
 Daily Factor Grp: 3
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9