

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2022

Site names: 00156  
 County: Butte  
 Funct Class: R Minor Arterial - Other  
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 3  
 Growth Factor Grp: 4

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	396	297	2	18	8	2	25	50	13	0	2	16	0
	Flex	.11	.00	.00	1.27	.70	.83	.26	.30	1.64	1.29	0.00	1.44	2.07	0.00
	Rigid	.24	.00	.00	1.66	.75	1.41	.47	.39	3.08	3.26	0.00	1.78	3.22	0.00
	GVW	9.0	2.8	5.2	36.0	19.3	27.3	30.2	21.1	54.4	75.8	0.0	43.6	66.7	0.0
E	Num	2	187	142	2	10	4	2	13	23	5	0	1	7	0
	Flex	.10	.01	.01	1.81	.80	1.51	.15	.44	1.94	1.48	0.00	.29	.89	0.00
	Rigid	.23	.01	.01	2.40	.86	2.70	.21	.55	3.83	3.50	0.00	.38	1.58	0.00
	GVW	8.5	3.3	5.9	36.2	21.0	34.3	31.0	24.0	56.3	73.9	0.0	30.1	46.6	0.0
W	Num	1	209	155	1	8	4	2	12	27	8	0	1	8	0
	Flex	.18	.00	.00	.87	.65	.34	.35	.14	1.33	1.34	0.00	2.68	2.46	0.00
	Rigid	.38	.00	.00	1.13	.69	.48	.72	.20	2.34	3.46	0.00	3.21	3.72	0.00
	GVW	12.7	2.3	4.4	35.9	17.5	21.1	28.1	17.9	52.0	77.3	0.0	61.8	79.5	0.0
E Lane1	Num	2	187	142	2	10	4	2	13	23	5	0	1	7	0
	Flex	.10	.01	.01	1.81	.80	1.51	.15	.44	1.94	1.48	0.00	.29	.89	0.00
	Rigid	.23	.01	.01	2.40	.86	2.70	.21	.55	3.83	3.50	0.00	.38	1.58	0.00
	GVW	8.5	3.3	5.9	36.2	21.0	34.3	31.0	24.0	56.3	73.9	0.0	30.1	46.6	0.0
W Lane1	Num	1	209	155	1	8	4	2	12	27	8	0	1	8	0
	Flex	.18	.00	.00	.87	.65	.34	.35	.14	1.33	1.34	0.00	2.68	2.46	0.00
	Rigid	.38	.00	.00	1.13	.69	.48	.72	.20	2.34	3.46	0.00	3.21	3.72	0.00
	GVW	12.7	2.3	4.4	35.9	17.5	21.1	28.1	17.9	52.0	77.3	0.0	61.8	79.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2022

Site names: 00156  
 County: Butte  
 Funct Class: R Minor Arterial - Other  
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 3  
 Growth Factor Grp: 4

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9