

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2022

Site names: 00156  
 County: Butte  
 Funct Class: R Minor Arterial - Other  
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 3  
 Growth Factor Grp: 4

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	326	252	3	14	7	2	25	50	16	1	2	14	0
	Flex	.12	.01	.01	.49	.38	.51	.30	.21	1.16	.82	.71	1.20	1.51	0.00
	Rigid	.27	.01	.01	.89	.38	.94	.77	.26	2.12	2.09	1.93	2.16	2.32	0.00
	GVW	10.3	3.4	5.1	33.9	19.2	31.8	48.9	24.2	59.7	77.9	73.1	66.1	81.4	0.0
E	Num	2	157	122	2	8	4	1	13	22	8	0	2	6	0
	Flex	.07	.00	.00	.43	.38	.71	.14	.23	1.25	.74	0.00	.56	.53	0.00
	Rigid	.15	.00	.00	.76	.39	1.37	.29	.27	2.41	1.75	0.00	.75	.82	0.00
	GVW	10.5	3.5	5.3	34.9	18.6	35.4	39.2	24.7	58.9	68.3	0.0	57.2	62.1	0.0
W	Num	2	169	130	2	7	3	1	12	28	9	1	1	9	0
	Flex	.22	.01	.01	.40	.37	.31	.29	.18	1.08	.88	.71	2.22	2.05	0.00
	Rigid	.51	.02	.01	.69	.37	.52	.76	.24	1.89	2.37	1.93	4.50	3.13	0.00
	GVW	10.2	3.4	4.9	27.4	19.6	28.9	47.1	23.6	60.1	86.2	73.1	87.6	92.5	0.0
E Lane1	Num	2	157	122	2	8	4	1	13	22	8	0	2	6	0
	Flex	.07	.00	.00	.43	.38	.71	.14	.23	1.25	.74	0.00	.56	.53	0.00
	Rigid	.15	.00	.00	.76	.39	1.37	.29	.27	2.41	1.75	0.00	.75	.82	0.00
	GVW	10.5	3.5	5.3	34.9	18.6	35.4	39.2	24.7	58.9	68.3	0.0	57.2	62.1	0.0
W Lane1	Num	2	169	130	2	7	3	1	12	28	9	1	1	9	0
	Flex	.22	.01	.01	.40	.37	.31	.29	.18	1.08	.88	.71	2.22	2.05	0.00
	Rigid	.51	.02	.01	.69	.37	.52	.76	.24	1.89	2.37	1.93	4.50	3.13	0.00
	GVW	10.2	3.4	4.9	27.4	19.6	28.9	47.1	23.6	60.1	86.2	73.1	87.6	92.5	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2022

Site names: 00156  
 County: Butte  
 Funct Class: R Minor Arterial - Other  
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: 3  
 Growth Factor Grp: 4

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9