

Idaho Transportation Department

Monthly WIM Distribution for Nov-2022

Site names: 00156
 County: Butte
 Funct Class: R Minor Arterial - Other
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 3
 Growth Factor Grp: 4

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	4	281	166	2	12	9	2	14	41	17	1	2	15	0
	Flex	.11	.01	.00	.86	.29	.36	.41	.19	1.06	.71	.77	.65	1.76	0.00
	Rigid	.24	.01	.00	1.19	.30	.65	1.16	.26	1.96	1.77	1.18	.90	2.59	0.00
	GVW	10.6	3.9	4.8	31.3	17.7	29.4	53.2	25.3	58.9	73.3	53.7	53.4	80.7	0.0
E	Num	2	146	75	1	6	4	1	8	19	8	1	2	6	0
	Flex	.13	.01	.00	.77	.23	.36	.41	.20	.86	.57	.91	1.17	.30	0.00
	Rigid	.29	.01	.00	1.08	.23	.65	1.11	.26	1.59	1.35	1.67	1.71	.47	0.00
	GVW	11.4	3.9	4.9	30.9	17.0	30.2	55.2	26.3	55.9	65.1	59.4	60.4	55.3	0.0
W	Num	3	135	91	1	6	4	2	7	22	8	1	1	9	0
	Flex	.09	.01	.01	.70	.38	.41	.38	.18	1.25	.93	.26	.66	2.67	0.00
	Rigid	.20	.02	.01	.94	.39	.72	.99	.25	2.33	2.37	.34	.85	3.87	0.00
	GVW	10.7	3.8	4.8	28.9	18.7	29.5	50.1	24.3	61.7	83.9	40.8	52.7	96.2	0.0
E Lane1	Num	2	146	75	1	6	4	1	8	19	8	1	2	6	0
	Flex	.13	.01	.00	.77	.23	.36	.41	.20	.86	.57	.91	1.17	.30	0.00
	Rigid	.29	.01	.00	1.08	.23	.65	1.11	.26	1.59	1.35	1.67	1.71	.47	0.00
	GVW	11.4	3.9	4.9	30.9	17.0	30.2	55.2	26.3	55.9	65.1	59.4	60.4	55.3	0.0
W Lane1	Num	3	135	91	1	6	4	2	7	22	8	1	1	9	0
	Flex	.09	.01	.01	.70	.38	.41	.38	.18	1.25	.93	.26	.66	2.67	0.00
	Rigid	.20	.02	.01	.94	.39	.72	.99	.25	2.33	2.37	.34	.85	3.87	0.00
	GVW	10.7	3.8	4.8	28.9	18.7	29.5	50.1	24.3	61.7	83.9	40.8	52.7	96.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Nov-2022

Site names: 00156
 County: Butte
 Funct Class: R Minor Arterial - Other
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 4
 Daily Factor Grp: 3
 Axle Factor Grp: 3
 Growth Factor Grp: 4

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9