

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2024

Site names: 00156  
 County: Butte  
 Funct Class: R Minor Arterial - Other  
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 4

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	3	264	162	2	10	6	2	12	40	25	1	2	43	0
	Flex	.16	.01	.00	.54	.29	.29	.16	.09	.89	.68	.11	.55	1.59	0.00
	Rigid	.33	.01	.00	.66	.29	.48	.37	.12	1.61	1.79	.11	.64	2.31	0.00
	GVW	16.4	3.6	4.5	23.9	16.9	26.7	42.3	21.2	54.7	77.7	26.9	45.1	86.2	0.0
E	Num	2	144	71	1	5	4	2	7	14	17	1	1	20	0
	Flex	.11	.01	.00	.33	.18	.21	.12	.09	.64	.65	.11	1.02	.46	0.00
	Rigid	.23	.01	.00	.38	.19	.38	.31	.11	1.27	1.75	.11	1.19	.89	0.00
	GVW	13.5	3.9	4.5	18.0	15.1	23.1	39.9	21.3	46.1	75.9	26.9	50.5	66.2	0.0
W	Num	1	120	91	2	5	3	1	5	26	8	0	1	23	0
	Flex	.31	.01	.00	.53	.39	.39	.44	.12	1.04	.64	0.00	.37	2.59	0.00
	Rigid	.66	.02	.00	.64	.39	.61	.88	.14	1.81	1.56	0.00	.41	3.50	0.00
	GVW	23.8	3.2	4.4	26.2	18.4	31.1	57.4	22.3	59.3	77.1	0.0	46.8	102.0	0.0
E Lane1	Num	2	144	71	1	5	4	2	7	14	17	1	1	20	0
	Flex	.11	.01	.00	.33	.18	.21	.12	.09	.64	.65	.11	1.02	.46	0.00
	Rigid	.23	.01	.00	.38	.19	.38	.31	.11	1.27	1.75	.11	1.19	.89	0.00
	GVW	13.5	3.9	4.5	18.0	15.1	23.1	39.9	21.3	46.1	75.9	26.9	50.5	66.2	0.0
W Lane1	Num	1	120	91	2	5	3	1	5	26	8	0	1	23	0
	Flex	.31	.01	.00	.53	.39	.39	.44	.12	1.04	.64	0.00	.37	2.59	0.00
	Rigid	.66	.02	.00	.64	.39	.61	.88	.14	1.81	1.56	0.00	.41	3.50	0.00
	GVW	23.8	3.2	4.4	26.2	18.4	31.1	57.4	22.3	59.3	77.1	0.0	46.8	102.0	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2024

Site names: 00156  
 County: Butte  
 Funct Class: R Minor Arterial - Other  
 Location: SH-33 6.0 Mi. E of Little Lost River Hwy

Seasonal Factor Grp: 4  
 Daily Factor Grp: 3  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 4

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9