

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2018

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	10	1,658	1,094	23	312	178	9	15	279	53	2	2	26	0
	Flex	.00	.00	.00	.74	.24	.74	.20	.49	1.13	.75	2.25	.27	.80	0.00
	Rigid	.00	.00	.00	.84	.27	1.34	.59	.66	2.05	1.65	2.35	.39	1.63	0.00
	GVW	3.0	4.0	6.5	23.0	18.1	32.7	42.3	30.7	55.5	65.7	53.9	42.3	72.6	0.0
N	Num	5	817	499	11	170	85	8	7	124	26	2	1	17	0
	Flex	.00	.00	.01	.64	.26	.42	.11	.29	.69	.40	.12	.24	.40	0.00
	Rigid	.00	.00	.01	.71	.29	.60	.38	.32	1.06	.75	.12	.25	.90	0.00
	GVW	3.4	4.2	6.6	21.7	17.5	26.0	37.7	26.3	46.3	53.5	27.4	41.1	63.5	0.0
S	Num	5	1,239	679	12	142	94	1	8	169	27	1	1	9	0
	Flex	.00	.00	.00	.83	.22	1.03	.58	.67	1.61	1.07	5.48	.35	1.46	0.00
	Rigid	.00	.00	.00	.96	.25	2.03	1.64	.98	3.06	2.46	5.82	.66	2.86	0.00
	GVW	2.3	4.2	6.5	24.0	18.9	38.9	58.9	34.9	66.0	76.3	83.7	45.2	87.4	0.0
N Lane1	Num	5	817	499	11	170	85	8	7	124	26	2	1	17	0
	Flex	.00	.00	.01	.64	.26	.42	.11	.29	.69	.40	.12	.24	.40	0.00
	Rigid	.00	.00	.01	.71	.29	.60	.38	.32	1.06	.75	.12	.25	.90	0.00
	GVW	3.4	4.2	6.6	21.7	17.5	26.0	37.7	26.3	46.3	53.5	27.4	41.1	63.5	0.0
S Lane1	Num	5	1,239	679	12	142	94	1	8	169	27	1	1	9	0
	Flex	.00	.00	.00	.83	.22	1.03	.58	.67	1.61	1.07	5.48	.35	1.46	0.00
	Rigid	.00	.00	.00	.96	.25	2.03	1.64	.98	3.06	2.46	5.82	.66	2.86	0.00
	GVW	2.3	4.2	6.5	24.0	18.9	38.9	58.9	34.9	66.0	76.3	83.7	45.2	87.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Oct-2018

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9