

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2019

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	7	1,852	1,260	11	419	21	2	18	185	35	1	1	27	0
	Flex	.00	.00	.00	.65	.16	.89	.42	.56	1.58	.71	5.40	.39	1.50	0.00
	Rigid	.00	.00	.00	.82	.16	1.63	1.54	.69	2.99	1.71	6.28	.40	2.70	0.00
	GVW	2.1	4.0	6.2	22.1	16.3	30.6	53.3	27.1	57.8	64.8	84.6	50.6	71.1	0.0
N	Num	5	1,251	891	7	49	15	2	7	122	23	1	1	20	0
	Flex	.00	.00	.00	.17	.09	.19	.10	.14	.35	.20	.80	.52	.27	0.00
	Rigid	.00	.00	.00	.18	.09	.29	.39	.16	.59	.43	.74	.53	.51	0.00
	GVW	1.2	3.4	5.9	19.2	16.0	24.6	43.5	23.8	46.4	50.9	56.1	55.2	55.6	0.0
S	Num	2	601	369	4	370	7	2	11	63	12	1	1	7	0
	Flex	.00	.00	.00	1.30	.17	2.46	.64	.90	3.86	1.85	7.70	.27	4.70	0.00
	Rigid	.00	.00	.00	1.67	.17	4.68	2.37	1.10	7.46	4.61	9.04	.28	8.66	0.00
	GVW	3.8	5.2	7.0	26.2	16.3	43.1	58.8	29.0	79.1	95.2	98.8	42.6	111.3	0.0
N Lane1	Num	5	1,251	891	7	49	15	2	7	122	23	1	1	20	0
	Flex	.00	.00	.00	.17	.09	.19	.10	.14	.35	.20	.80	.52	.27	0.00
	Rigid	.00	.00	.00	.18	.09	.29	.39	.16	.59	.43	.74	.53	.51	0.00
	GVW	1.2	3.4	5.9	19.2	16.0	24.6	43.5	23.8	46.4	50.9	56.1	55.2	55.6	0.0
S Lane1	Num	2	601	369	4	370	7	2	11	63	12	1	1	7	0
	Flex	.00	.00	.00	1.30	.17	2.46	.64	.90	3.86	1.85	7.70	.27	4.70	0.00
	Rigid	.00	.00	.00	1.67	.17	4.68	2.37	1.10	7.46	4.61	9.04	.28	8.66	0.00
	GVW	3.8	5.2	7.0	26.2	16.3	43.1	58.8	29.0	79.1	95.2	98.8	42.6	111.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2019

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9