

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	5	1,658	1,175	21	391	79	5	14	176	54	1	1	34	0
	Flex	.00	.00	.00	.43	.14	.55	.50	.39	1.04	.60	.71	.37	.66	0.00
	Rigid	.00	.00	.00	.48	.14	1.02	1.60	.46	1.91	1.40	.69	.38	1.31	0.00
	GVW	2.0	3.8	6.3	21.1	16.2	31.7	51.2	26.0	54.3	66.2	38.7	51.7	69.1	0.0
N	Num	4	1,290	906	15	60	64	4	8	140	43	1	1	30	0
	Flex	.00	.00	.00	.26	.10	.37	.22	.24	.43	.33	.04	.37	.39	0.00
	Rigid	.00	.00	.00	.30	.10	.67	.72	.28	.75	.74	.04	.37	.79	0.00
	GVW	1.2	3.4	6.0	20.7	16.3	30.2	47.2	26.9	48.5	60.2	25.6	51.7	64.6	0.0
S	Num	2	368	269	6	331	15	2	7	36	12	1	1	5	0
	Flex	.00	.00	.00	.87	.14	1.57	1.14	.58	3.58	1.86	1.39	.58	2.41	0.00
	Rigid	.00	.00	.00	1.00	.14	3.05	3.62	.67	6.91	4.34	1.34	.57	4.84	0.00
	GVW	4.4	5.2	7.2	21.9	16.0	41.2	62.2	25.1	79.5	89.7	51.8	50.9	101.6	0.0
N Lane1	Num	4	1,290	906	15	60	64	4	8	140	43	1	1	30	0
	Flex	.00	.00	.00	.26	.10	.37	.22	.24	.43	.33	.04	.37	.39	0.00
	Rigid	.00	.00	.00	.30	.10	.67	.72	.28	.75	.74	.04	.37	.79	0.00
	GVW	1.2	3.4	6.0	20.7	16.3	30.2	47.2	26.9	48.5	60.2	25.6	51.7	64.6	0.0
S Lane1	Num	2	368	269	6	331	15	2	7	36	12	1	1	5	0
	Flex	.00	.00	.00	.87	.14	1.57	1.14	.58	3.58	1.86	1.39	.58	2.41	0.00
	Rigid	.00	.00	.00	1.00	.14	3.05	3.62	.67	6.91	4.34	1.34	.57	4.84	0.00
	GVW	4.4	5.2	7.2	21.9	16.0	41.2	62.2	25.1	79.5	89.7	51.8	50.9	101.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2019

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9