

Idaho Transportation Department

Monthly WIM Distribution for Dec-2019

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,657	1,122	20	415	19	1	13	191	35	2	1	24	0
	Flex	.00	.00	.00	1.53	.12	1.93	1.79	.89	2.97	1.44	2.36	.57	2.37	0.00
	Rigid	.00	.00	.00	2.28	.12	3.46	5.91	1.19	6.00	3.62	3.45	.57	4.86	0.00
	GVW	3.0	4.0	6.4	28.0	14.8	40.5	76.1	31.8	69.6	84.7	40.9	56.5	87.8	0.0
N	Num	1	1,104	706	12	65	13	2	7	116	24	2	1	17	0
	Flex	.00	.00	.00	.40	.13	.70	.13	.34	.90	.74	.10	.59	.71	0.00
	Rigid	.00	.00	.00	.43	.13	1.10	.50	.36	1.51	1.66	.09	.59	1.52	0.00
	GVW	1.6	3.6	6.1	21.3	15.5	33.7	43.4	28.6	56.0	74.3	26.5	57.5	70.2	0.0
S	Num	2	553	416	9	351	5	1	6	75	11	1	1	7	0
	Flex	.00	.00	.00	2.92	.12	4.99	2.41	1.44	6.95	3.48	11.06	.51	7.61	0.00
	Rigid	.00	.00	.00	4.61	.12	9.12	7.27	1.99	14.53	9.17	16.06	.52	14.88	0.00
	GVW	5.7	5.0	7.0	36.0	14.6	57.5	84.7	34.8	95.1	112.5	101.1	47.8	136.9	0.0
N Lane1	Num	1	1,104	706	12	65	13	2	7	116	24	2	1	17	0
	Flex	.00	.00	.00	.40	.13	.70	.13	.34	.90	.74	.10	.59	.71	0.00
	Rigid	.00	.00	.00	.43	.13	1.10	.50	.36	1.51	1.66	.09	.59	1.52	0.00
	GVW	1.6	3.6	6.1	21.3	15.5	33.7	43.4	28.6	56.0	74.3	26.5	57.5	70.2	0.0
S Lane1	Num	2	553	416	9	351	5	1	6	75	11	1	1	7	0
	Flex	.00	.00	.00	2.92	.12	4.99	2.41	1.44	6.95	3.48	11.06	.51	7.61	0.00
	Rigid	.00	.00	.00	4.61	.12	9.12	7.27	1.99	14.53	9.17	16.06	.52	14.88	0.00
	GVW	5.7	5.0	7.0	36.0	14.6	57.5	84.7	34.8	95.1	112.5	101.1	47.8	136.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Dec-2019

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9