

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,691	1,004	19	352	22	2	13	201	28	1	2	18	0
	Flex	.00	.00	.00	1.85	.17	1.78	.98	1.13	3.37	1.68	.85	1.71	2.85	0.00
	Rigid	.00	.00	.00	2.62	.18	3.24	3.42	1.31	6.39	4.02	.81	2.03	6.74	0.00
	GVW	2.7	4.1	6.6	30.3	15.3	41.4	71.2	33.8	74.0	83.3	45.1	62.0	100.2	0.0
N	Num	1	1,186	662	12	105	15	2	8	135	19	1	1	12	0
	Flex	.00	.00	.00	.76	.19	1.14	.67	.94	1.90	.83	1.67	.67	1.72	0.00
	Rigid	.00	.00	.00	.84	.21	1.96	2.46	1.08	3.25	1.77	1.60	.69	3.70	0.00
	GVW	1.7	3.8	6.4	26.0	15.8	37.1	66.8	32.8	65.7	69.8	66.4	56.5	86.3	0.0
S	Num	1	505	342	8	247	7	1	5	66	9	1	1	6	0
	Flex	.02	.00	.00	3.02	.16	3.57	1.41	1.35	7.35	4.18	.03	2.25	6.68	0.00
	Rigid	.02	.00	.00	4.51	.17	6.86	4.64	1.57	14.80	10.69	.03	2.72	16.19	0.00
	GVW	5.2	5.0	6.9	35.4	15.1	53.3	75.7	33.4	95.9	121.7	23.7	67.1	136.7	0.0
N Lane1	Num	1	1,186	662	12	105	15	2	8	135	19	1	1	12	0
	Flex	.00	.00	.00	.76	.19	1.14	.67	.94	1.90	.83	1.67	.67	1.72	0.00
	Rigid	.00	.00	.00	.84	.21	1.96	2.46	1.08	3.25	1.77	1.60	.69	3.70	0.00
	GVW	1.7	3.8	6.4	26.0	15.8	37.1	66.8	32.8	65.7	69.8	66.4	56.5	86.3	0.0
S Lane1	Num	1	505	342	8	247	7	1	5	66	9	1	1	6	0
	Flex	.02	.00	.00	3.02	.16	3.57	1.41	1.35	7.35	4.18	.03	2.25	6.68	0.00
	Rigid	.02	.00	.00	4.51	.17	6.86	4.64	1.57	14.80	10.69	.03	2.72	16.19	0.00
	GVW	5.2	5.0	6.9	35.4	15.1	53.3	75.7	33.4	95.9	121.7	23.7	67.1	136.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2020

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9