

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2020

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3,814	2,425	1,977	12	153	66	6	29	314	71	0	1	51	0
	Flex	.05	.00	.00	.66	.07	.21	.15	.18	.33	.19	0.00	.19	.51	0.00
	Rigid	.08	.00	.00	.80	.07	.36	.36	.23	.58	.39	0.00	.20	.86	0.00
	GVW	7.8	3.2	5.9	26.9	15.9	27.1	42.0	27.5	45.3	48.6	0.0	47.3	64.5	0.0
N	Num	2,347	1,398	1,095	8	72	30	2	16	175	39	0	1	31	0
	Flex	.02	.00	.00	.12	.07	.07	.19	.19	.20	.11	0.00	.19	.23	0.00
	Rigid	.03	.00	.00	.15	.07	.11	.28	.24	.34	.20	0.00	.20	.44	0.00
	GVW	7.0	3.3	6.0	20.2	15.4	20.9	45.5	28.6	41.6	40.7	0.0	47.3	56.5	0.0
S	Num	1,467	1,027	882	4	81	36	4	13	139	32	0	0	20	0
	Flex	.09	.00	.00	1.73	.08	.33	.14	.17	.49	.28	0.00	0.00	.93	0.00
	Rigid	.15	.00	.00	2.09	.08	.56	.40	.22	.87	.63	0.00	0.00	1.53	0.00
	GVW	9.0	3.2	5.8	40.3	16.4	32.2	40.3	26.3	49.9	58.1	0.0	0.0	76.8	0.0
N Lane1	Num	2,347	1,398	1,095	8	72	30	2	16	175	39	0	1	31	0
	Flex	.02	.00	.00	.12	.07	.07	.19	.19	.20	.11	0.00	.19	.23	0.00
	Rigid	.03	.00	.00	.15	.07	.11	.28	.24	.34	.20	0.00	.20	.44	0.00
	GVW	7.0	3.3	6.0	20.2	15.4	20.9	45.5	28.6	41.6	40.7	0.0	47.3	56.5	0.0
S Lane1	Num	1,467	1,027	882	4	81	36	4	13	139	32	0	0	20	0
	Flex	.09	.00	.00	1.73	.08	.33	.14	.17	.49	.28	0.00	0.00	.93	0.00
	Rigid	.15	.00	.00	2.09	.08	.56	.40	.22	.87	.63	0.00	0.00	1.53	0.00
	GVW	9.0	3.2	5.8	40.3	16.4	32.2	40.3	26.3	49.9	58.1	0.0	0.0	76.8	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Jul-2020

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 2  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9