

Idaho Transportation Department

Monthly WIM Distribution for Sep-2022

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	7	3,262	1,668	5	66	100	8	75	352	88	1	4	32	0
	Flex	.03	.00	.00	.66	.39	.37	.53	.19	1.02	.65	.96	.85	1.55	0.00
	Rigid	.06	.00	.00	.95	.38	.66	1.33	.23	1.93	1.63	1.46	1.46	2.37	0.00
	GVW	3.4	2.5	4.7	38.2	19.1	31.3	55.9	24.4	61.5	75.2	60.1	63.5	80.9	0.0
N	Num	5	1,652	833	2	34	51	5	38	167	45	1	2	16	0
	Flex	.02	.00	.00	.50	.33	.41	.44	.21	.95	.73	1.49	1.79	.77	0.00
	Rigid	.05	.00	.00	.65	.32	.75	1.15	.25	1.77	1.85	3.62	2.67	1.31	0.00
	GVW	2.8	2.7	4.9	33.9	18.8	32.6	54.7	25.0	61.6	78.9	84.7	78.6	69.3	0.0
S	Num	3	1,610	835	4	32	49	3	38	185	43	1	3	16	0
	Flex	.03	.00	.00	.80	.45	.33	.66	.18	1.11	.52	.82	.62	2.20	0.00
	Rigid	.06	.00	.00	1.14	.45	.59	1.52	.22	2.11	1.29	.92	1.19	3.24	0.00
	GVW	4.0	2.3	4.5	40.8	19.5	30.3	60.4	23.8	61.4	69.2	53.9	61.1	90.3	0.0
N Lane1	Num	5	1,652	833	2	34	51	5	38	167	45	1	2	16	0
	Flex	.02	.00	.00	.50	.33	.41	.44	.21	.95	.73	1.49	1.79	.77	0.00
	Rigid	.05	.00	.00	.65	.32	.75	1.15	.25	1.77	1.85	3.62	2.67	1.31	0.00
	GVW	2.8	2.7	4.9	33.9	18.8	32.6	54.7	25.0	61.6	78.9	84.7	78.6	69.3	0.0
S Lane1	Num	3	1,610	835	4	32	49	3	38	185	43	1	3	16	0
	Flex	.03	.00	.00	.80	.45	.33	.66	.18	1.11	.52	.82	.62	2.20	0.00
	Rigid	.06	.00	.00	1.14	.45	.59	1.52	.22	2.11	1.29	.92	1.19	3.24	0.00
	GVW	4.0	2.3	4.5	40.8	19.5	30.3	60.4	23.8	61.4	69.2	53.9	61.1	90.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Sep-2022

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 2
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9