

Idaho Transportation Department

Monthly WIM Distribution for Jan-2023

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	2,528	1,290	4	52	47	6	44	256	51	1	3	23	0
	Flex	.22	.00	.00	.73	.29	.40	.51	.23	1.02	.67	1.55	1.37	1.32	0.00
	Rigid	.45	.00	.00	.97	.28	.67	1.32	.27	1.92	1.71	3.85	2.36	2.07	0.00
	GVW	19.5	2.3	4.1	33.2	17.9	32.8	63.2	26.6	62.7	78.1	86.9	77.0	80.8	0.0
N	Num	1	1,341	657	2	26	24	4	22	118	27	0	2	12	0
	Flex	.19	.00	.00	.40	.30	.45	.40	.30	1.03	.81	0.00	1.05	.57	0.00
	Rigid	.40	.00	.00	.51	.30	.78	1.03	.36	1.94	2.04	0.00	1.76	.95	0.00
	GVW	19.2	2.5	4.4	24.9	18.4	34.3	53.2	28.7	62.9	78.2	0.0	68.5	63.3	0.0
S	Num	2	1,187	633	3	26	23	3	22	138	25	1	2	12	0
	Flex	.28	.00	.00	.78	.28	.37	.60	.15	1.03	.50	1.55	1.59	1.84	0.00
	Rigid	.58	.00	.00	1.04	.27	.59	1.53	.19	1.92	1.30	3.85	2.73	2.82	0.00
	GVW	19.4	2.0	3.8	34.6	17.6	31.7	68.7	24.2	62.7	76.6	86.9	82.9	93.7	0.0
N Lane1	Num	1	1,341	657	2	26	24	4	22	118	27	0	2	12	0
	Flex	.19	.00	.00	.40	.30	.45	.40	.30	1.03	.81	0.00	1.05	.57	0.00
	Rigid	.40	.00	.00	.51	.30	.78	1.03	.36	1.94	2.04	0.00	1.76	.95	0.00
	GVW	19.2	2.5	4.4	24.9	18.4	34.3	53.2	28.7	62.9	78.2	0.0	68.5	63.3	0.0
S Lane1	Num	2	1,187	633	3	26	23	3	22	138	25	1	2	12	0
	Flex	.28	.00	.00	.78	.28	.37	.60	.15	1.03	.50	1.55	1.59	1.84	0.00
	Rigid	.58	.00	.00	1.04	.27	.59	1.53	.19	1.92	1.30	3.85	2.73	2.82	0.00
	GVW	19.4	2.0	3.8	34.6	17.6	31.7	68.7	24.2	62.7	76.6	86.9	82.9	93.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2023

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9