

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2023

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	5	3,140	1,694	5	77	61	8	68	279	82	1	3	28	0
	Flex	.10	.00	.00	.60	.29	.42	.53	.18	1.04	.60	.82	.95	1.17	0.00
	Rigid	.21	.00	.00	.75	.29	.73	1.43	.22	1.91	1.51	1.23	1.82	2.18	0.00
	GVW	8.2	2.4	4.4	32.6	17.9	32.1	63.2	23.6	61.4	73.2	60.3	68.4	83.3	0.0
N	Num	4	1,630	865	3	40	30	5	35	138	40	1	2	19	0
	Flex	.08	.00	.00	.71	.31	.52	.35	.25	1.09	.76	.88	1.22	.65	0.00
	Rigid	.17	.00	.00	.97	.31	.93	.96	.29	1.98	1.94	2.22	1.96	1.24	0.00
	GVW	6.6	2.6	4.7	36.8	18.5	34.2	52.3	25.8	62.4	79.9	76.0	69.6	73.5	0.0
S	Num	2	1,510	829	3	37	31	4	33	142	42	1	2	9	0
	Flex	.08	.00	.00	.52	.27	.32	.60	.12	.99	.43	.78	1.12	1.54	0.00
	Rigid	.17	.00	.00	.60	.27	.51	1.66	.15	1.86	1.07	.74	2.13	2.67	0.00
	GVW	8.3	2.1	4.0	29.0	17.2	30.0	70.3	21.2	60.4	66.2	52.4	73.4	89.4	0.0
N Lane1	Num	4	1,630	865	3	40	30	5	35	138	40	1	2	19	0
	Flex	.08	.00	.00	.71	.31	.52	.35	.25	1.09	.76	.88	1.22	.65	0.00
	Rigid	.17	.00	.00	.97	.31	.93	.96	.29	1.98	1.94	2.22	1.96	1.24	0.00
	GVW	6.6	2.6	4.7	36.8	18.5	34.2	52.3	25.8	62.4	79.9	76.0	69.6	73.5	0.0
S Lane1	Num	2	1,510	829	3	37	31	4	33	142	42	1	2	9	0
	Flex	.08	.00	.00	.52	.27	.32	.60	.12	.99	.43	.78	1.12	1.54	0.00
	Rigid	.17	.00	.00	.60	.27	.51	1.66	.15	1.86	1.07	.74	2.13	2.67	0.00
	GVW	8.3	2.1	4.0	29.0	17.2	30.0	70.3	21.2	60.4	66.2	52.4	73.4	89.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2023

Site names: 00169  
 County: Payette  
 Funct Class: R Principal Arterial - Other  
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9