

Idaho Transportation Department

Monthly WIM Distribution for Jan-2024

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	16	2,341	1,365	9	66	57	7	35	219	39	3	2	16	0
	Flex	.04	.00	.00	.63	.18	.34	.27	.22	.97	.63	.96	1.55	.88	0.00
	Rigid	.08	.00	.00	.74	.18	.58	.87	.26	1.81	1.60	.90	2.41	1.62	0.00
	GVW	12.2	2.3	3.9	30.0	15.7	32.0	50.4	25.7	62.4	79.1	56.8	76.5	79.2	0.0
N	Num	6	1,176	702	4	33	26	4	17	103	21	3	2	9	0
	Flex	.05	.00	.00	.50	.18	.33	.34	.29	.94	.57	.96	1.43	.71	0.00
	Rigid	.12	.00	.00	.61	.18	.56	1.02	.35	1.74	1.39	.90	1.60	1.25	0.00
	GVW	12.9	2.4	4.1	26.8	15.5	32.0	49.6	27.8	62.1	76.3	56.8	68.2	67.7	0.0
S	Num	10	1,165	663	5	33	30	5	17	116	18	0	1	8	0
	Flex	.03	.00	.00	.63	.18	.35	.23	.15	1.00	.66	0.00	1.46	1.03	0.00
	Rigid	.06	.00	.00	.77	.18	.60	.83	.17	1.88	1.71	0.00	2.43	1.91	0.00
	GVW	11.9	2.1	3.7	32.0	15.8	32.2	50.4	23.6	62.6	80.7	0.0	76.2	88.9	0.0
N Lane1	Num	6	1,176	702	4	33	26	4	17	103	21	3	2	9	0
	Flex	.05	.00	.00	.50	.18	.33	.34	.29	.94	.57	.96	1.43	.71	0.00
	Rigid	.12	.00	.00	.61	.18	.56	1.02	.35	1.74	1.39	.90	1.60	1.25	0.00
	GVW	12.9	2.4	4.1	26.8	15.5	32.0	49.6	27.8	62.1	76.3	56.8	68.2	67.7	0.0
S Lane1	Num	10	1,165	663	5	33	30	5	17	116	18	0	1	8	0
	Flex	.03	.00	.00	.63	.18	.35	.23	.15	1.00	.66	0.00	1.46	1.03	0.00
	Rigid	.06	.00	.00	.77	.18	.60	.83	.17	1.88	1.71	0.00	2.43	1.91	0.00
	GVW	11.9	2.1	3.7	32.0	15.8	32.2	50.4	23.6	62.6	80.7	0.0	76.2	88.9	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jan-2024

Site names: 00169
 County: Payette
 Funct Class: R Principal Arterial - Other
 Location: US-95 2.4 Mi. N of Jct US-20

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 1

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
N Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
S Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9