

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2017

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	1,494	998	2	36	59	3	21	261	196	1	4	387	0
	Flex	.00	.00	.00	.20	.75	.71	.66	.26	.91	1.01	.39	.18	1.21	0.00
	Rigid	.00	.00	.00	.21	.80	1.25	1.08	.39	1.73	2.45	.53	.18	2.13	0.00
	GVW	1.9	3.4	4.3	23.8	19.9	31.1	47.6	22.9	49.8	74.1	25.4	34.7	78.5	0.0
SE	Num	1	767	510	1	20	30	3	10	138	94	1	4	194	0
	Flex	.00	.00	.00	.35	.42	.82	.63	.23	.69	.69	.33	.16	.16	0.00
	Rigid	.00	.00	.00	.33	.43	1.51	.95	.31	1.26	1.51	.40	.16	.20	0.00
	GVW	3.0	3.4	4.4	22.3	17.2	33.4	47.4	20.5	46.2	62.0	36.2	33.9	38.4	0.0
NW	Num	1	727	488	1	15	29	1	11	123	102	1	1	193	0
	Flex	.00	.00	.00	.17	1.20	.58	.56	.32	1.16	1.26	.50	.42	2.26	0.00
	Rigid	.00	.00	.00	.19	1.31	.98	1.19	.50	2.26	3.18	.71	.42	4.08	0.00
	GVW	1.7	3.4	4.2	23.2	23.7	28.3	36.7	25.4	53.7	83.4	25.8	46.4	119.1	0.0
NW Lane1	Num	1	727	488	1	15	29	1	11	123	102	1	1	193	0
	Flex	.00	.00	.00	.17	1.20	.58	.56	.32	1.16	1.26	.50	.42	2.26	0.00
	Rigid	.00	.00	.00	.19	1.31	.98	1.19	.50	2.26	3.18	.71	.42	4.08	0.00
	GVW	1.7	3.4	4.2	23.2	23.7	28.3	36.7	25.4	53.7	83.4	25.8	46.4	119.1	0.0
SE Lane1	Num	1	767	510	1	20	30	3	10	138	94	1	4	194	0
	Flex	.00	.00	.00	.35	.42	.82	.63	.23	.69	.69	.33	.16	.16	0.00
	Rigid	.00	.00	.00	.33	.43	1.51	.95	.31	1.26	1.51	.40	.16	.20	0.00
	GVW	3.0	3.4	4.4	22.3	17.2	33.4	47.4	20.5	46.2	62.0	36.2	33.9	38.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2017

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9