

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2017

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	1,649	1,130	2	39	86	3	26	284	197	2	1	109	0
	Flex	.00	.00	.00	.27	.69	.83	.72	.21	.92	1.02	.16	.82	1.95	0.00
	Rigid	.00	.00	.00	.28	.73	1.55	1.19	.28	1.73	2.55	.15	.90	2.89	0.00
	GVW	2.0	3.3	4.3	13.3	19.6	32.0	47.2	21.9	48.6	73.9	22.3	48.3	72.8	0.0
SE	Num	1	841	574	1	22	44	2	12	154	91	1	1	56	0
	Flex	.00	.00	.00	.49	.45	.53	.73	.15	.55	.72	.18	.20	.69	0.00
	Rigid	.00	.00	.00	.52	.47	.99	.96	.22	.95	1.52	.18	.23	1.05	0.00
	GVW	2.4	3.3	4.4	14.7	18.0	28.5	44.6	20.4	42.3	60.8	24.8	36.8	55.3	0.0
NW	Num	1	808	556	1	17	42	3	14	130	106	1	1	53	0
	Flex	.00	.00	.00	.18	.94	1.15	.75	.27	1.41	1.20	.06	.84	3.36	0.00
	Rigid	.00	.00	.00	.18	1.03	2.16	1.22	.35	2.78	3.17	.07	.92	4.92	0.00
	GVW	1.4	3.3	4.2	16.8	21.0	35.8	43.1	23.1	57.0	82.0	17.1	52.7	91.8	0.0
NW Lane1	Num	1	808	556	1	17	42	3	14	130	106	1	1	53	0
	Flex	.00	.00	.00	.18	.94	1.15	.75	.27	1.41	1.20	.06	.84	3.36	0.00
	Rigid	.00	.00	.00	.18	1.03	2.16	1.22	.35	2.78	3.17	.07	.92	4.92	0.00
	GVW	1.4	3.3	4.2	16.8	21.0	35.8	43.1	23.1	57.0	82.0	17.1	52.7	91.8	0.0
SE Lane1	Num	1	841	574	1	22	44	2	12	154	91	1	1	56	0
	Flex	.00	.00	.00	.49	.45	.53	.73	.15	.55	.72	.18	.20	.69	0.00
	Rigid	.00	.00	.00	.52	.47	.99	.96	.22	.95	1.52	.18	.23	1.05	0.00
	GVW	2.4	3.3	4.4	14.7	18.0	28.5	44.6	20.4	42.3	60.8	24.8	36.8	55.3	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Apr-2017

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9