

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,793	1,207	1	30	84	5	44	223	144	2	2	59	0
	Flex	.00	.00	.00	.10	.70	.59	.79	.18	.93	1.02	.29	1.36	1.94	0.00
	Rigid	.00	.00	.00	.18	.74	1.06	1.15	.23	1.72	2.35	.58	1.91	2.73	0.00
	GVW	1.6	3.6	4.2	9.5	19.8	29.9	39.3	16.7	49.8	74.4	27.9	55.5	68.0	0.0
SE	Num	1	918	612	1	15	42	4	22	116	69	1	1	33	0
	Flex	.00	.00	.00	.00	.64	.72	.45	.16	.59	.96	.16	4.52	.81	0.00
	Rigid	.00	.00	.00	.00	.68	1.34	.75	.21	1.00	2.03	.24	7.11	1.18	0.00
	GVW	1.7	3.7	4.1	2.5	19.4	32.3	36.7	16.5	41.9	67.0	27.0	85.3	51.8	0.0
NW	Num	2	875	595	2	15	44	2	22	107	75	1	1	27	0
	Flex	.00	.00	.00	.14	.74	.47	1.21	.20	1.33	1.05	.34	.44	3.36	0.00
	Rigid	.00	.00	.00	.26	.79	.79	1.64	.25	2.56	2.59	.73	.44	4.65	0.00
	GVW	1.4	3.4	4.3	13.0	20.1	27.4	41.8	16.8	58.8	79.9	24.6	41.9	87.3	0.0
NW Lane1	Num	2	875	595	2	15	44	2	22	107	75	1	1	27	0
	Flex	.00	.00	.00	.14	.74	.47	1.21	.20	1.33	1.05	.34	.44	3.36	0.00
	Rigid	.00	.00	.00	.26	.79	.79	1.64	.25	2.56	2.59	.73	.44	4.65	0.00
	GVW	1.4	3.4	4.3	13.0	20.1	27.4	41.8	16.8	58.8	79.9	24.6	41.9	87.3	0.0
SE Lane1	Num	1	918	612	1	15	42	4	22	116	69	1	1	33	0
	Flex	.00	.00	.00	.00	.64	.72	.45	.16	.59	.96	.16	4.52	.81	0.00
	Rigid	.00	.00	.00	.00	.68	1.34	.75	.21	1.00	2.03	.24	7.11	1.18	0.00
	GVW	1.7	3.7	4.1	2.5	19.4	32.3	36.7	16.5	41.9	67.0	27.0	85.3	51.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2017

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9