

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,303	814	1	22	22	2	12	192	145	2	5	332	0
	Flex	.00	.00	.00	.22	.64	.49	1.50	.19	.73	.81	.30	1.45	.94	0.00
	Rigid	.00	.00	.00	.30	.67	.76	1.82	.23	1.35	1.92	.37	2.17	1.77	0.00
	GVW	1.7	3.5	4.2	23.1	20.0	27.4	35.4	20.9	47.4	71.2	36.3	60.1	78.0	0.0
SE	Num	2	660	418	1	13	12	1	6	108	64	1	2	169	0
	Flex	.00	.00	.00	.25	.55	.34	1.56	.19	.42	.63	.35	.24	.18	0.00
	Rigid	.00	.00	.00	.36	.57	.48	1.85	.23	.70	1.35	.43	.25	.23	0.00
	GVW	2.2	3.5	4.3	25.2	19.7	26.7	36.6	20.5	40.3	56.8	34.5	39.4	38.7	0.0
NW	Num	1	643	396	1	9	10	1	6	84	81	2	3	163	0
	Flex	.00	.00	.00	.19	.75	.70	1.85	.21	1.17	.96	.14	2.75	1.74	0.00
	Rigid	.00	.00	.00	.25	.80	1.14	2.20	.24	2.26	2.38	.25	4.21	3.37	0.00
	GVW	1.7	3.5	4.0	21.0	20.6	28.8	34.5	22.5	57.6	81.2	35.3	82.7	118.7	0.0
NW Lane1	Num	1	643	396	1	9	10	1	6	84	81	2	3	163	0
	Flex	.00	.00	.00	.19	.75	.70	1.85	.21	1.17	.96	.14	2.75	1.74	0.00
	Rigid	.00	.00	.00	.25	.80	1.14	2.20	.24	2.26	2.38	.25	4.21	3.37	0.00
	GVW	1.7	3.5	4.0	21.0	20.6	28.8	34.5	22.5	57.6	81.2	35.3	82.7	118.7	0.0
SE Lane1	Num	2	660	418	1	13	12	1	6	108	64	1	2	169	0
	Flex	.00	.00	.00	.25	.55	.34	1.56	.19	.42	.63	.35	.24	.18	0.00
	Rigid	.00	.00	.00	.36	.57	.48	1.85	.23	.70	1.35	.43	.25	.23	0.00
	GVW	2.2	3.5	4.3	25.2	19.7	26.7	36.6	20.5	40.3	56.8	34.5	39.4	38.7	0.0

Idaho Transportation Department

Monthly WIM Distribution for Feb-2019

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9