

Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,570	969	2	24	48	3	17	209	192	2	3	244	0
	Flex	.00	.00	.00	.43	.63	.55	1.16	.28	.89	.90	.04	.65	1.14	0.00
	Rigid	.00	.00	.00	.52	.66	.93	1.44	.38	1.69	2.13	.04	.92	1.93	0.00
	GVW	1.6	3.5	4.1	24.5	19.8	27.6	35.7	24.3	48.1	72.1	22.6	47.6	73.9	0.0
SE	Num	1	801	495	1	13	25	2	8	116	88	1	2	124	0
	Flex	.00	.00	.00	.59	.64	.78	1.29	.26	.63	.90	.04	.34	.66	0.00
	Rigid	.00	.00	.00	.70	.67	1.42	1.52	.36	1.17	2.05	.04	.36	1.00	0.00
	GVW	2.1	3.5	4.2	28.9	20.2	31.1	37.4	22.8	41.6	64.9	20.0	42.9	49.3	0.0
NW	Num	2	769	474	1	11	23	1	9	93	104	2	2	120	0
	Flex	.00	.00	.00	.28	.63	.31	1.19	.29	1.22	.88	.03	.99	1.59	0.00
	Rigid	.00	.00	.00	.32	.68	.42	1.49	.38	2.35	2.14	.04	1.48	2.80	0.00
	GVW	1.4	3.4	4.1	22.1	19.5	23.7	32.4	24.9	56.3	76.6	25.2	55.2	96.9	0.0
NW Lane1	Num	2	769	474	1	11	23	1	9	93	104	2	2	120	0
	Flex	.00	.00	.00	.28	.63	.31	1.19	.29	1.22	.88	.03	.99	1.59	0.00
	Rigid	.00	.00	.00	.32	.68	.42	1.49	.38	2.35	2.14	.04	1.48	2.80	0.00
	GVW	1.4	3.4	4.1	22.1	19.5	23.7	32.4	24.9	56.3	76.6	25.2	55.2	96.9	0.0
SE Lane1	Num	1	801	495	1	13	25	2	8	116	88	1	2	124	0
	Flex	.00	.00	.00	.59	.64	.78	1.29	.26	.63	.90	.04	.34	.66	0.00
	Rigid	.00	.00	.00	.70	.67	1.42	1.52	.36	1.17	2.05	.04	.36	1.00	0.00
	GVW	2.1	3.5	4.2	28.9	20.2	31.1	37.4	22.8	41.6	64.9	20.0	42.9	49.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2019

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9