

Idaho Transportation Department

Monthly WIM Distribution for Jun-2019

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3	1,798	1,204	3	34	72	6	46	251	148	2	2	46	0
	Flex	.00	.00	.00	1.17	.76	.69	.72	.19	1.06	1.09	.04	.83	1.74	0.00
	Rigid	.00	.00	.00	1.76	.82	1.18	1.45	.24	2.02	2.67	.04	.96	2.56	0.00
	GVW	2.1	3.8	4.0	39.7	19.6	31.1	46.5	17.4	50.9	78.9	19.5	55.6	64.6	0.0
SE	Num	1	925	611	2	17	36	4	24	141	63	2	1	24	0
	Flex	.00	.00	.00	1.12	.63	.65	.89	.21	.68	.84	.04	4.34	.70	0.00
	Rigid	.00	.00	.00	1.88	.67	1.14	1.56	.26	1.24	1.88	.05	4.59	1.11	0.00
	GVW	1.8	3.9	4.0	42.7	18.7	31.8	49.2	16.8	44.4	67.1	22.4	87.5	52.2	0.0
NW	Num	2	874	593	2	17	36	3	22	110	85	1	1	22	0
	Flex	.00	.00	.00	1.17	.85	.75	.83	.18	1.56	1.24	.03	.48	3.06	0.00
	Rigid	.00	.00	.00	1.69	.92	1.27	1.75	.24	3.08	3.18	.04	.59	4.48	0.00
	GVW	2.2	3.6	4.0	38.2	20.5	30.6	46.3	18.2	59.5	86.4	15.3	53.5	81.9	0.0
NW Lane1	Num	2	874	593	2	17	36	3	22	110	85	1	1	22	0
	Flex	.00	.00	.00	1.17	.85	.75	.83	.18	1.56	1.24	.03	.48	3.06	0.00
	Rigid	.00	.00	.00	1.69	.92	1.27	1.75	.24	3.08	3.18	.04	.59	4.48	0.00
	GVW	2.2	3.6	4.0	38.2	20.5	30.6	46.3	18.2	59.5	86.4	15.3	53.5	81.9	0.0
SE Lane1	Num	1	925	611	2	17	36	4	24	141	63	2	1	24	0
	Flex	.00	.00	.00	1.12	.63	.65	.89	.21	.68	.84	.04	4.34	.70	0.00
	Rigid	.00	.00	.00	1.88	.67	1.14	1.56	.26	1.24	1.88	.05	4.59	1.11	0.00
	GVW	1.8	3.9	4.0	42.7	18.7	31.8	49.2	16.8	44.4	67.1	22.4	87.5	52.2	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2019

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9