

Idaho Transportation Department

Monthly WIM Distribution for Jul-2019

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,773	1,167	1	33	67	6	43	206	97	2	1	43	0
	Flex	.00	.00	.00	.33	.71	.54	.67	.22	1.24	1.13	.07	.38	2.20	0.00
	Rigid	.00	.00	.00	.45	.77	.87	1.41	.29	2.45	2.74	.06	.39	3.41	0.00
	GVW	1.7	3.8	4.0	17.3	20.4	28.6	44.2	17.2	52.9	75.3	21.3	39.6	65.0	0.0
SE	Num	1	906	595	1	17	34	4	22	109	48	2	1	22	0
	Flex	.00	.00	.00	1.30	.77	.61	.64	.17	.77	.97	.07	.61	.60	0.00
	Rigid	.00	.00	.00	1.88	.83	1.04	1.26	.25	1.41	2.15	.06	.62	.96	0.00
	GVW	1.9	3.9	4.0	31.4	20.1	30.4	44.1	15.7	45.3	68.9	22.5	42.7	49.0	0.0
NW	Num	2	867	572	1	16	33	4	21	98	48	1	2	21	0
	Flex	.00	.00	.00	.22	.73	.48	.72	.26	1.80	1.28	.10	.34	4.18	0.00
	Rigid	.00	.00	.00	.28	.79	.72	1.24	.34	3.67	3.20	.09	.35	6.48	0.00
	GVW	1.7	3.7	3.9	18.2	21.2	27.0	38.2	18.7	61.3	79.9	23.0	39.8	85.0	0.0
NW Lane1	Num	2	867	572	1	16	33	4	21	98	48	1	2	21	0
	Flex	.00	.00	.00	.22	.73	.48	.72	.26	1.80	1.28	.10	.34	4.18	0.00
	Rigid	.00	.00	.00	.28	.79	.72	1.24	.34	3.67	3.20	.09	.35	6.48	0.00
	GVW	1.7	3.7	3.9	18.2	21.2	27.0	38.2	18.7	61.3	79.9	23.0	39.8	85.0	0.0
SE Lane1	Num	1	906	595	1	17	34	4	22	109	48	2	1	22	0
	Flex	.00	.00	.00	1.30	.77	.61	.64	.17	.77	.97	.07	.61	.60	0.00
	Rigid	.00	.00	.00	1.88	.83	1.04	1.26	.25	1.41	2.15	.06	.62	.96	0.00
	GVW	1.9	3.9	4.0	31.4	20.1	30.4	44.1	15.7	45.3	68.9	22.5	42.7	49.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jul-2019

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9