

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2019

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,695	1,100	1	38	129	3	28	228	161	3	2	321	0
	Flex	.00	.00	.00	.09	2.20	1.55	1.40	1.09	4.00	2.99	.64	2.73	5.72	0.00
	Rigid	.00	.00	.00	.09	2.50	2.52	2.13	1.42	7.70	6.73	.78	3.18	11.63	0.00
	GVW	2.9	3.6	3.5	8.6	26.6	35.6	44.4	29.3	68.6	91.3	27.2	69.4	107.7	0.0
SE	Num	2	872	559	1	20	67	2	14	118	97	2	1	180	0
	Flex	.00	.00	.00	.13	.83	.54	.63	.24	1.10	1.34	.03	3.07	.53	0.00
	Rigid	.00	.00	.00	.13	.88	1.04	1.12	.31	2.22	3.18	.04	3.50	.86	0.00
	GVW	2.0	3.7	4.1	7.6	21.7	27.0	43.0	19.5	50.7	78.2	17.8	73.9	48.1	0.0
NW	Num	2	823	542	1	18	62	1	14	110	65	2	1	140	0
	Flex	.00	.00	.00	.00	3.78	2.66	2.73	1.90	7.18	5.14	2.00	2.39	12.49	0.00
	Rigid	.00	.00	.00	.01	4.38	4.20	3.80	2.48	13.78	11.20	2.45	2.86	25.69	0.00
	GVW	3.0	3.5	2.9	8.4	32.4	44.7	43.9	38.1	88.6	105.4	46.2	66.1	185.7	0.0
NW Lane1	Num	2	823	542	1	18	62	1	14	110	65	2	1	140	0
	Flex	.00	.00	.00	.00	3.78	2.66	2.73	1.90	7.18	5.14	2.00	2.39	12.49	0.00
	Rigid	.00	.00	.00	.01	4.38	4.20	3.80	2.48	13.78	11.20	2.45	2.86	25.69	0.00
	GVW	3.0	3.5	2.9	8.4	32.4	44.7	43.9	38.1	88.6	105.4	46.2	66.1	185.7	0.0
SE Lane1	Num	2	872	559	1	20	67	2	14	118	97	2	1	180	0
	Flex	.00	.00	.00	.13	.83	.54	.63	.24	1.10	1.34	.03	3.07	.53	0.00
	Rigid	.00	.00	.00	.13	.88	1.04	1.12	.31	2.22	3.18	.04	3.50	.86	0.00
	GVW	2.0	3.7	4.1	7.6	21.7	27.0	43.0	19.5	50.7	78.2	17.8	73.9	48.1	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Sep-2019

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9