

Idaho Transportation Department

Monthly WIM Distribution for Mar-2020

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,432	982	2	27	63	3	21	241	138	1	2	111	0
	Flex	.00	.00	.00	.29	1.05	.76	1.30	.29	.90	1.07	.03	.31	1.38	0.00
	Rigid	.00	.00	.00	.34	1.16	1.43	1.64	.38	1.70	2.55	.03	.32	2.02	0.00
	GVW	2.3	3.6	4.1	18.8	21.2	29.0	35.6	23.3	49.6	74.9	17.1	40.5	67.7	0.0
SE	Num	1	735	499	2	14	33	2	10	122	73	1	1	58	0
	Flex	.00	.00	.00	.29	.91	.96	.78	.28	.75	1.02	.01	.29	.73	0.00
	Rigid	.00	.00	.00	.34	.98	1.88	1.08	.34	1.39	2.28	.02	.31	1.14	0.00
	GVW	2.4	3.6	4.1	18.8	21.2	31.9	39.9	21.3	45.8	71.9	16.4	39.9	52.3	0.0
NW	Num	2	698	483	0	13	30	2	11	119	65	1	3	53	0
	Flex	.00	.00	.00	0.00	1.18	.54	1.52	.30	1.07	1.10	.04	.33	2.08	0.00
	Rigid	.00	.00	.00	0.00	1.33	.96	1.82	.41	2.05	2.77	.04	.34	2.95	0.00
	GVW	2.3	3.6	4.1	0.0	21.0	25.9	29.2	25.4	53.8	76.4	18.6	41.0	83.2	0.0
NW Lane1	Num	2	698	483	0	13	30	2	11	119	65	1	3	53	0
	Flex	.00	.00	.00	0.00	1.18	.54	1.52	.30	1.07	1.10	.04	.33	2.08	0.00
	Rigid	.00	.00	.00	0.00	1.33	.96	1.82	.41	2.05	2.77	.04	.34	2.95	0.00
	GVW	2.3	3.6	4.1	0.0	21.0	25.9	29.2	25.4	53.8	76.4	18.6	41.0	83.2	0.0
SE Lane1	Num	1	735	499	2	14	33	2	10	122	73	1	1	58	0
	Flex	.00	.00	.00	.29	.91	.96	.78	.28	.75	1.02	.01	.29	.73	0.00
	Rigid	.00	.00	.00	.34	.98	1.88	1.08	.34	1.39	2.28	.02	.31	1.14	0.00
	GVW	2.4	3.6	4.1	18.8	21.2	31.9	39.9	21.3	45.8	71.9	16.4	39.9	52.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2020

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9