

Idaho Transportation Department

Monthly WIM Distribution for Jun-2020

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3	1,705	1,176	1	30	75	4	47	227	120	2	2	54	0
	Flex	.00	.00	.00	.07	.73	.59	1.01	.34	1.01	1.02	1.30	.21	1.54	0.00
	Rigid	.00	.00	.00	.11	.78	.94	1.63	.41	1.94	2.52	1.54	.23	2.27	0.00
	GVW	2.3	3.8	4.0	12.4	19.2	28.1	42.3	17.9	50.0	77.3	31.6	34.6	68.9	0.0
SE	Num	1	879	603	1	15	39	4	24	124	50	1	1	31	0
	Flex	.00	.00	.00	.28	.79	.69	1.11	.26	.61	.88	.19	.09	.78	0.00
	Rigid	.00	.00	.00	.48	.85	1.20	1.84	.32	1.08	1.99	.47	.10	1.26	0.00
	GVW	1.9	3.9	4.0	34.8	19.6	29.7	46.5	17.7	42.4	64.7	29.7	30.6	59.0	0.0
NW	Num	2	827	574	1	15	37	3	23	103	70	1	2	23	0
	Flex	.00	.00	.00	.02	.64	.49	.97	.38	1.58	1.06	2.86	.68	2.41	0.00
	Rigid	.00	.00	.00	.02	.68	.69	1.58	.46	3.16	2.69	3.24	.71	3.37	0.00
	GVW	2.5	3.6	4.0	6.8	18.6	26.5	38.9	18.0	59.8	82.5	37.8	46.0	77.7	0.0
NW Lane1	Num	2	827	574	1	15	37	3	23	103	70	1	2	23	0
	Flex	.00	.00	.00	.02	.64	.49	.97	.38	1.58	1.06	2.86	.68	2.41	0.00
	Rigid	.00	.00	.00	.02	.68	.69	1.58	.46	3.16	2.69	3.24	.71	3.37	0.00
	GVW	2.5	3.6	4.0	6.8	18.6	26.5	38.9	18.0	59.8	82.5	37.8	46.0	77.7	0.0
SE Lane1	Num	1	879	603	1	15	39	4	24	124	50	1	1	31	0
	Flex	.00	.00	.00	.28	.79	.69	1.11	.26	.61	.88	.19	.09	.78	0.00
	Rigid	.00	.00	.00	.48	.85	1.20	1.84	.32	1.08	1.99	.47	.10	1.26	0.00
	GVW	1.9	3.9	4.0	34.8	19.6	29.7	46.5	17.7	42.4	64.7	29.7	30.6	59.0	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2020

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp:

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9