

Idaho Transportation Department

Monthly WIM Distribution for Jun-2021

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	3	1,973	1,371	4	33	70	4	65	201	154	2	1	40	0
	Flex	.00	.00	.00	.36	.68	.77	.68	.19	.94	1.02	.04	.83	1.75	0.00
	Rigid	.00	.00	.00	.41	.73	1.26	1.06	.26	1.71	2.49	.04	.93	2.66	0.00
	GVW	2.3	3.9	4.0	21.0	19.4	31.8	35.9	17.5	49.4	74.9	19.4	47.2	68.2	0.0
SE	Num	2	1,010	703	4	17	36	2	33	112	72	1	1	22	0
	Flex	.00	.00	.00	1.80	.76	1.04	.83	.17	.70	.99	.06	.76	1.10	0.00
	Rigid	.00	.00	.00	1.99	.81	1.78	1.10	.24	1.18	2.22	.08	.83	1.73	0.00
	GVW	2.5	4.0	4.0	30.3	20.2	35.3	34.5	17.2	44.1	67.1	23.6	47.1	60.1	0.0
NW	Num	2	963	669	3	16	35	4	31	88	82	1	1	18	0
	Flex	.00	.00	.00	.13	.61	.53	.42	.20	1.25	1.03	.02	1.59	2.58	0.00
	Rigid	.00	.00	.00	.16	.65	.80	.91	.28	2.37	2.66	.02	2.16	3.86	0.00
	GVW	2.2	3.8	3.9	19.2	18.8	28.5	37.0	17.7	56.4	80.5	16.4	55.1	78.6	0.0
NW Lane1	Num	2	963	669	3	16	35	4	31	88	82	1	1	18	0
	Flex	.00	.00	.00	.13	.61	.53	.42	.20	1.25	1.03	.02	1.59	2.58	0.00
	Rigid	.00	.00	.00	.16	.65	.80	.91	.28	2.37	2.66	.02	2.16	3.86	0.00
	GVW	2.2	3.8	3.9	19.2	18.8	28.5	37.0	17.7	56.4	80.5	16.4	55.1	78.6	0.0
SE Lane1	Num	2	1,010	703	4	17	36	2	33	112	72	1	1	22	0
	Flex	.00	.00	.00	1.80	.76	1.04	.83	.17	.70	.99	.06	.76	1.10	0.00
	Rigid	.00	.00	.00	1.99	.81	1.78	1.10	.24	1.18	2.22	.08	.83	1.73	0.00
	GVW	2.5	4.0	4.0	30.3	20.2	35.3	34.5	17.2	44.1	67.1	23.6	47.1	60.1	0.0

Idaho Transportation Department

Monthly WIM Distribution for Jun-2021

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9