

Idaho Transportation Department

Monthly WIM Distribution for Mar-2022

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFSC
Road	Num	2	1,667	972	2	24	60	5	18	236	169	5	2	277	0
	Flex	.00	.00	.00	.41	.81	.43	1.39	.23	.87	.78	3.70	1.15	1.34	0.00
	Rigid	.00	.00	.00	.53	.89	.74	1.74	.28	1.62	1.83	4.08	1.27	2.37	0.00
	GVW	1.8	3.7	3.9	30.5	21.7	25.5	36.3	21.6	48.5	70.9	54.1	56.7	78.0	0.0
SE	Num	1	851	495	1	13	30	4	9	129	78	2	1	141	0
	Flex	.00	.00	.00	.32	.98	.58	.51	.22	.54	.69	.11	1.51	.49	0.00
	Rigid	.00	.00	.00	.39	1.08	1.05	.79	.28	.92	1.50	.11	1.72	.85	0.00
	GVW	2.0	3.9	3.9	28.8	23.6	27.9	38.6	21.7	42.0	62.1	27.6	66.0	49.6	0.0
NW	Num	2	816	478	1	11	30	2	9	106	92	3	1	148	0
	Flex	.00	.00	.00	.76	.74	.29	1.26	.24	1.29	.84	7.33	.90	2.18	0.00
	Rigid	.00	.00	.00	1.04	.81	.43	1.52	.28	2.49	2.06	8.07	.98	3.78	0.00
	GVW	2.1	3.6	3.9	33.8	20.0	23.1	32.4	21.8	56.8	76.2	80.5	51.7	107.9	0.0
NW Lane1	Num	2	816	478	1	11	30	2	9	106	92	3	1	148	0
	Flex	.00	.00	.00	.76	.74	.29	1.26	.24	1.29	.84	7.33	.90	2.18	0.00
	Rigid	.00	.00	.00	1.04	.81	.43	1.52	.28	2.49	2.06	8.07	.98	3.78	0.00
	GVW	2.1	3.6	3.9	33.8	20.0	23.1	32.4	21.8	56.8	76.2	80.5	51.7	107.9	0.0
SE Lane1	Num	1	851	495	1	13	30	4	9	129	78	2	1	141	0
	Flex	.00	.00	.00	.32	.98	.58	.51	.22	.54	.69	.11	1.51	.49	0.00
	Rigid	.00	.00	.00	.39	1.08	1.05	.79	.28	.92	1.50	.11	1.72	.85	0.00
	GVW	2.0	3.9	3.9	28.8	23.6	27.9	38.6	21.7	42.0	62.1	27.6	66.0	49.6	0.0

Idaho Transportation Department

Monthly WIM Distribution for Mar-2022

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus 0.4 Mi. SE of Marina Rd

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: 3
 Growth Factor Grp: 5

		UNCL
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9