

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2022

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,445	972	1	31	38	4	18	191	88	2	3	367	0
	Flex	.00	.00	.00	1.68	.66	.55	.26	.25	.78	.84	.07	.51	1.08	0.00
	Rigid	.00	.00	.00	2.18	.89	.90	.40	.40	1.42	1.90	.17	.54	2.05	0.00
	GVW	2.1	3.8	3.9	32.7	26.6	28.7	33.0	24.3	48.7	69.0	17.3	40.8	80.6	0.0
SE	Num	1	741	501	1	17	19	3	9	97	45	1	1	191	0
	Flex	.00	.00	.00	2.06	.45	.73	.29	.22	.47	.63	.14	.47	.18	0.00
	Rigid	.00	.00	.00	3.54	.54	1.29	.44	.35	.80	1.35	.32	.55	.25	0.00
	GVW	1.8	3.8	4.1	53.4	22.4	32.8	33.9	22.9	42.5	61.4	19.6	43.8	40.9	0.0
NW	Num	2	704	471	1	15	19	1	10	94	43	2	2	176	0
	Flex	.00	.00	.00	1.48	.88	.39	.16	.37	1.12	.97	.02	.63	2.05	0.00
	Rigid	.00	.00	.00	1.82	1.23	.53	.24	.64	2.09	2.26	.03	.65	3.99	0.00
	GVW	2.2	3.9	3.8	28.4	30.7	25.2	27.1	28.6	55.4	73.2	17.2	42.2	123.6	0.0
NW Lane1	Num	2	704	471	1	15	19	1	10	94	43	2	2	176	0
	Flex	.00	.00	.00	1.48	.88	.39	.16	.37	1.12	.97	.02	.63	2.05	0.00
	Rigid	.00	.00	.00	1.82	1.23	.53	.24	.64	2.09	2.26	.03	.65	3.99	0.00
	GVW	2.2	3.9	3.8	28.4	30.7	25.2	27.1	28.6	55.4	73.2	17.2	42.2	123.6	0.0
SE Lane1	Num	1	741	501	1	17	19	3	9	97	45	1	1	191	0
	Flex	.00	.00	.00	2.06	.45	.73	.29	.22	.47	.63	.14	.47	.18	0.00
	Rigid	.00	.00	.00	3.54	.54	1.29	.44	.35	.80	1.35	.32	.55	.25	0.00
	GVW	1.8	3.8	4.1	53.4	22.4	32.8	33.9	22.9	42.5	61.4	19.6	43.8	40.9	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Nov-2022

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: 3  
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9