

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2024

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,841	1,349	3	32	65	3	22	213	197	2	1	482	0
	Flex	.00	.00	.00	1.56	.64	.63	.60	.35	.75	.99	.31	.78	1.11	0.00
	Rigid	.00	.00	.00	2.06	.68	1.02	.89	.47	1.35	2.31	.51	1.08	2.14	0.00
	GVW	3.0	3.7	3.9	37.8	19.3	28.2	35.4	24.8	47.2	70.4	30.1	41.8	77.9	0.0
SE	Num	1	951	698	2	17	34	2	10	116	93	1	1	247	0
	Flex	.00	.00	.00	1.74	.60	.70	.37	.35	.46	.60	.46	.78	.18	0.00
	Rigid	.00	.00	.00	2.34	.65	1.21	.52	.45	.76	1.27	.72	1.12	.22	0.00
	GVW	1.9	3.7	4.1	38.6	19.2	30.4	32.8	24.0	41.6	58.4	45.0	45.9	40.4	0.0
NW	Num	2	889	652	2	15	31	2	12	98	103	2	1	235	0
	Flex	.00	.00	.00	.87	.73	.56	.65	.37	1.18	1.28	.21	.28	2.07	0.00
	Rigid	.00	.00	.00	1.22	.77	.84	1.01	.52	2.22	3.06	.33	.28	4.12	0.00
	GVW	3.0	3.8	3.8	35.9	19.5	26.2	34.4	25.5	54.8	78.2	21.9	32.9	117.0	0.0
NW Lane1	Num	2	889	652	2	15	31	2	12	98	103	2	1	235	0
	Flex	.00	.00	.00	.87	.73	.56	.65	.37	1.18	1.28	.21	.28	2.07	0.00
	Rigid	.00	.00	.00	1.22	.77	.84	1.01	.52	2.22	3.06	.33	.28	4.12	0.00
	GVW	3.0	3.8	3.8	35.9	19.5	26.2	34.4	25.5	54.8	78.2	21.9	32.9	117.0	0.0
SE Lane1	Num	1	951	698	2	17	34	2	10	116	93	1	1	247	0
	Flex	.00	.00	.00	1.74	.60	.70	.37	.35	.46	.60	.46	.78	.18	0.00
	Rigid	.00	.00	.00	2.34	.65	1.21	.52	.45	.76	1.27	.72	1.12	.22	0.00
	GVW	1.9	3.7	4.1	38.6	19.2	30.4	32.8	24.0	41.6	58.4	45.0	45.9	40.4	0.0

# Idaho Transportation Department

## Monthly WIM Distribution for Mar-2024

Site names: 00179  
 County: Power  
 Funct Class: R Minor Arterial - Other  
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2  
 Daily Factor Grp: 2  
 Axle Factor Grp: All\_Class\_Sites  
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9