

Idaho Transportation Department

Monthly WIM Distribution for Apr-2024

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 5

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	2	1,978	1,478	2	46	95	8	34	262	247	2	2	249	0
	Flex	.00	.00	.00	.62	.76	.64	1.01	.27	.78	.92	.11	.22	1.36	0.00
	Rigid	.00	.00	.00	.87	.82	1.07	1.39	.39	1.42	2.09	.12	.23	2.12	0.00
	GVW	2.7	3.9	3.9	25.7	19.6	29.5	43.5	22.8	48.4	69.5	16.9	30.2	69.9	0.0
SE	Num	1	1,022	764	2	25	46	6	16	141	121	1	1	130	0
	Flex	.00	.00	.00	.94	.76	.61	.94	.26	.57	.76	.02	.96	.50	0.00
	Rigid	.00	.00	.00	1.54	.82	1.06	1.30	.39	.99	1.66	.02	1.06	.75	0.00
	GVW	1.9	4.0	4.0	28.0	19.5	30.8	46.0	22.7	44.8	65.8	15.9	48.2	48.8	0.0
NW	Num	2	957	714	1	21	49	3	17	120	126	1	2	119	0
	Flex	.00	.00	.00	.83	.80	.70	1.04	.27	1.04	1.04	.34	.16	2.45	0.00
	Rigid	.00	.00	.00	1.10	.86	1.12	1.38	.38	1.93	2.42	.37	.16	3.79	0.00
	GVW	3.1	3.8	3.9	30.3	20.1	28.6	36.5	22.9	52.7	72.2	21.2	28.1	93.3	0.0
NW Lane1	Num	2	957	714	1	21	49	3	17	120	126	1	2	119	0
	Flex	.00	.00	.00	.83	.80	.70	1.04	.27	1.04	1.04	.34	.16	2.45	0.00
	Rigid	.00	.00	.00	1.10	.86	1.12	1.38	.38	1.93	2.42	.37	.16	3.79	0.00
	GVW	3.1	3.8	3.9	30.3	20.1	28.6	36.5	22.9	52.7	72.2	21.2	28.1	93.3	0.0
SE Lane1	Num	1	1,022	764	2	25	46	6	16	141	121	1	1	130	0
	Flex	.00	.00	.00	.94	.76	.61	.94	.26	.57	.76	.02	.96	.50	0.00
	Rigid	.00	.00	.00	1.54	.82	1.06	1.30	.39	.99	1.66	.02	1.06	.75	0.00
	GVW	1.9	4.0	4.0	28.0	19.5	30.8	46.0	22.7	44.8	65.8	15.9	48.2	48.8	0.0

Idaho Transportation Department

Monthly WIM Distribution for Apr-2024

Site names: 00179
 County: Power
 Funct Class: R Minor Arterial - Other
 Location: I-86 Bus, American Falls, .6 Mi. W. of SH-39/Pocatello Ave Jct

Seasonal Factor Grp: 2
 Daily Factor Grp: 2
 Axle Factor Grp: All_Class_Sites
 Growth Factor Grp: 5

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
NW Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
SE Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9