

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		MC	CAR	PU	BUS	2D	SU 3	SU 4+	ST 4-	ST 5	ST 6+	MT 5-	MT 6	MT 7+	OFFSCALE
Road	Num	1	348	241	2	4	3	1	7	20	23	1	1	11	0
	Flex	.00	.00	.00	.61	.33	.31	.83	.27	1.11	.42	.09	.46	.78	0.00
	Rigid	.00	.00	.00	.76	.32	.45	.88	.28	1.77	1.26	.12	.50	1.30	0.00
	GVW	1.5	4.6	3.8	29.6	18.7	28.0	29.7	21.9	59.3	86.0	24.0	54.1	74.8	0.0
E	Num	2	172	121	1	2	2	1	4	11	9	1	1	6	0
	Flex	.00	.00	.00	.60	.41	.56	1.11	.29	1.53	.53	.06	.64	.85	0.00
	Rigid	.00	.00	.00	.88	.41	.89	1.21	.30	2.50	1.40	.09	.70	1.24	0.00
	GVW	1.7	4.6	3.4	34.7	19.6	32.0	32.3	21.3	68.3	78.0	24.9	62.0	64.3	0.0
W	Num	1	176	120	2	3	2	1	3	9	15	1	2	6	0
	Flex	.00	.00	.00	.48	.23	.20	.60	.25	.49	.34	.24	.11	.68	0.00
	Rigid	.00	.00	.00	.54	.22	.27	.63	.27	.72	1.13	.27	.14	1.33	0.00
	GVW	1.5	4.5	4.1	21.9	18.0	25.3	29.3	23.4	46.1	90.3	26.7	38.5	85.3	0.0
E Lane1	Num	2	172	121	1	2	2	1	4	11	9	1	1	6	0
	Flex	.00	.00	.00	.60	.41	.56	1.11	.29	1.53	.53	.06	.64	.85	0.00
	Rigid	.00	.00	.00	.88	.41	.89	1.21	.30	2.50	1.40	.09	.70	1.24	0.00
	GVW	1.7	4.6	3.4	34.7	19.6	32.0	32.3	21.3	68.3	78.0	24.9	62.0	64.3	0.0
W Lane1	Num	1	176	120	2	3	2	1	3	9	15	1	2	6	0
	Flex	.00	.00	.00	.48	.23	.20	.60	.25	.49	.34	.24	.11	.68	0.00
	Rigid	.00	.00	.00	.54	.22	.27	.63	.27	.72	1.13	.27	.14	1.33	0.00
	GVW	1.5	4.5	4.1	21.9	18.0	25.3	29.3	23.4	46.1	90.3	26.7	38.5	85.3	0.0

Idaho Transportation Department

Monthly WIM Distribution for May-2017

Site names: 00185
 County: Idaho
 Funct Class: R Principal Arterial - Other
 Location: US-12 0.2 Mi. NE. of Powell Ranger Station

Seasonal Factor Grp: 10
 Daily Factor Grp: 5
 Axle Factor Grp: 2
 Growth Factor Grp:

		UNCLS
Road	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
E Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0
W Lane1	Num	0
	Flex	0.00
	Rigid	0.00
	GVW	0.0

Flex ESALs are calculated using Servicability=2.5, SN=5. Rigid ESALs use Servicability=2.5, Depth=9